

# EAPO: Enhancing Policy Optimization with On-Demand Expert Assistance

Siyao Song\*, Cong Ma†, Zhihao Cheng, Shiye Lei, Minghao Li, Ying Zeng, Huaixiao Tou, Kai Jia

ByteDance BandAI 

songsiyao2024@ia.ac.cn, {macong.13, zhihao.cheng, leishiye, liminghao.bd, zengying.ss, zhangyuan.zhang, jiakai}@bytedance.com

## Abstract

Large language models (LLMs) have recently advanced in reasoning when optimized with reinforcement learning (RL) under verifiable rewards. Existing methods primarily rely on outcome-based supervision to strengthen internal LLM reasoning, often leading to inefficient exploration and sparse rewards. To mitigate this issue, we propose *Expert-Assisted Policy Optimization* (EAPO), a novel RL framework that enhances exploration by incorporating multi-turn interactions with external experts during training. Unlike prior methods, where policies reason in isolation, EAPO incentivizes the policy to adaptively determine when and how to consult experts, yielding richer reward signals and more reliable reasoning trajectories. External assistance ultimately internalizes expert knowledge into the policy model, amplifying the model’s inherent reasoning capabilities. During evaluation, the policy model has been well-optimized to solve questions independently, producing improved reasoning paths and more accurate solutions. Experiments on mathematical reasoning benchmarks, including AIME 2024, AIME 2025, and AIMO 2025, show that EAPO consistently outperforms expert-assisted workflow, expert-distilled models, and RL baselines, with an average gain of 5 points over self-exploratory models.

## 1 Introduction

Large reasoning models (LRMs) have recently achieved remarkable progress in areas such as mathematics and logical reasoning. However, guiding these models to produce accurate multi-step reasoning chains remains a major challenge, as it involves broad search spaces, sparse feedback and unstable optimization process (Ouyang et al., 2022; Christiano et al., 2017; Gou et al., 2023). Existing post-training frameworks typically optimize models with supervised fine-tuning (SFT) and subsequently refine models through reinforcement learning from human feedback (RLHF) to better align model outputs with human preferences (Ouyang et al., 2022). Although effective in various applications, RLHF methods suffer from reward hacking, over-optimization on proxy objectives, and instability during training (Gao et al., 2023; Casper et al., 2023).

Reasoning models are particularly sensitive to these challenges, leading to high exploration costs and unstable behavior when optimized for complex reasoning tasks. Various reward designs are proposed to alleviate these problems: verifiable rewards provide objective re-

\*Work done during an internship at ByteDance.

†Corresponding Author




Figure 1: Framework of EAPO. During training, the policy model adaptively consults experts as assistants. While at test time, model performs reasoning independently without external assistance.

ward signals that help alleviate reward hacking (Lambert et al., 2024). Rita et al. (2024) mitigates reward over-optimization by using rewards calibrated with demonstrations, while Barj & Sautory (2024) leverages feedback from LLMs to remedy objective mis-generalization. Although these reward signals are more robust in recent research, existing reinforcement learning (RL) algorithms rely on policy model to explore and exploit on its own to produce long chains of thought, resulting in inefficient exploration and suboptimal optimization. To enhance reasoning performance during evaluation, recent methods incorporate parallel sampling or aggregation of multiple candidate reasoning trajectories (Kumar et al., 2024), such as self-Consistency (Wang et al., 2022), Tree-of-Thoughts (Yao et al., 2023), Mixture-of-Agents (Wang et al., 2024), and LeaP (Luo et al., 2025). Despite improving solution quality, heavy communication cost and implementation complexity are still unsolved and capacity of the policy model is not improved in these test-time scaling based methods.

To address these limitations, we propose *Expert-Assisted Policy Optimization* (EAPO), a novel RL optimization framework that adaptively integrates consulting experts into the model’s decision making process, as illustrated in Figure 1. Specifically, the agent’s action space is augmented with a special *consult experts* action, which enables agent improve its reasoning strategy when external assistance is needed. The policy model can therefore choose either to generate the reasoning tokens independently or to seek a hint from experts. When the *consult experts* action is utilized, the external expert pool provides the assistant responses, prompting the reasoning process of policy model. Additionally, to prevent the agent from over-relying on expert assistance, *consult experts* operation is regarded as a learnable action and optimized jointly with reasoning actions.

During RL optimization, the model is progressively encouraged to rely on its own reasoning ability, ensuring that consultant occurs on demand only when the agent encounters difficult questions or ambiguous reasoning paths. With a curriculum-like optimization design, the agent is allowed to consult experts freely without in the early stages of training, providing richer assistance compared to the sparse feedback from final verifiable rewards. Experimental observations show that policy model gradually learns to consult experts only for challenging questions, rather than relying on assistance for all cases. Moreover, responses from experts help policy model to take deeper reasoning by consolidating multi-perspective insights. This design significantly improves agent’s advanced reasoning strategies, such as summarization, judgment and reasoning, which are rarely observed in self-exploratory models. To further strengthen the model’s own capability, a penalty term on consultation is introduced. As training progresses, the model is incentivized to consult less frequently, internalizing the consulted reasoning strategies into its own reasoning process. With sufficient training, EAPO effectively internalizes expert knowledge into policy model, eliminating the need for consultation during evaluation.

In our experiments, we comprehensively evaluate three datasets on mathematical reasoning, including AIME 2024, AIME 2025 and AIMO 2025. Compared with various strong baselines, such as expert-assisted workflow, distillation from experts and self-exploratory RL models, EAPO gains consistent improvements on all these benchmarks with a significant improvement of 5 points over self-exploratory RL on averaged evaluation results. Furthermore, training with assistance from experts, policy model achieves lower variance on test sets, indicating greater stability and consistency in its reasoning performance. Our contributions are summarized as follows:

- **Expert-Assisted Optimization:** Expert consultation is designed as a learnable action within the policy, enabling the model to consult assistance on demand during training. This mechanism guides the reasoning trajectory throughout exploration and improves optimization efficiency compared to supervision based solely on final verifiable rewards.
- **Assistance Internalization:** EAPO progressively reduces the reliance on expert assistance throughout training, encouraging the model to internalize expert knowledge into its own reasoning process. During evaluation, the policy model responds entirely independently, yet still demonstrates strong reasoning performance.
- **Enhanced Reasoning Performance:** Extensive experiments on challenging reasoning benchmarks (AIME 2024/2025, AIMO 2025) demonstrate that EAPO achieves superior accuracy and stability. Ablation studies and analyses further show that EAPO consistently improves reasoning performance as expert parallelism and model size scale up.

## 2 Expert-Assisted Policy Optimization (EAPO)

### 2.1 Problem Formalization

We consider a complex reasoning task with input  $x$  and ground truth answer  $g$ . A reasoning process can be formalized as a trajectory

$$H_T = \{(\tau_i, \alpha_i, o_i)\}_{i=1}^T,$$

where  $\tau_t$  represents the intermediate reasoning chain,  $\alpha_t$  is the policy action that determines whether and how to consult the expert or produce the final answer, and  $o_t$  denotes the assistance from experts at step  $t$ . If the policy calls the expert, then  $o_t$  corresponds to the expert’s feedback; otherwise,  $o_t = \emptyset$ . Given the current trajectory  $H_t = \{(\tau_i, \alpha_i, o_i)\}_{i=1}^t$ , the policy model  $\pi_\theta$ , parameterized by  $\theta$ , generates  $\tau_t$  and  $\alpha_t$  at step  $t$  as

$$\pi_\theta(\tau_t, \alpha_t | H_{t-1}) = \pi_\theta^\tau(\tau_t | H_{t-1}) \cdot \pi_\theta^\alpha(\alpha_t | H_{t-1}, \tau_t),$$

where  $\pi_\theta^\tau$  and  $\pi_\theta^\alpha$  denote the probability of intermediate reasoning chain and the consultation decision, respectively. During testing,  $\alpha$  is fixed to prevent expert consultation, ensuring that the policy model performs reasoning independently without expert assistance. Therefore, given an input  $x$ , the probability of generating the entire trajectory can be computed as

$$\pi_\theta(H_T | x) = \prod_{t=0}^{T-1} \pi_\theta^\tau(\tau_{t+1} | H_t) \cdot \pi_\theta^\alpha(\alpha_{t+1} | H_t, \tau_{t+1}) \cdot p(o_{t+1} | \alpha_{t+1}),$$

where  $H_0 = x$  denotes the initial input, and  $p(o_{t+1} | \alpha_{t+1})$  is the probability of assistance returned by experts.

Once the full trajectory  $H_T$  is generated by  $\pi_\theta$ , the output answer  $\hat{y}$  is extracted from the last reasoning step using a pre-defined extraction rule, *i.e.*,  $\hat{y} = \mathcal{E}(H_T)$ . The reward function follows an end-to-end verifiable reward design. Given  $\hat{y}$  and the ground truth be  $g$ , the reward is obtained as

$$R = \begin{cases} \text{f1}(\hat{y}, g) & \text{if f1 score is not 0,} \\ 0.1 & \text{if f1 score is 0 with correct format} \\ 0 & \text{otherwise} \end{cases}$$

Given the training dataset  $\mathcal{D}$  consisting of  $(x, g)$  pairs, the objective of EAPO can be defined as

$$\max_{\theta} \mathcal{J}_{\text{EAPO}} = \mathbb{E}_{(x,g) \sim \mathcal{D}, H_T \sim \pi_{\theta}(\cdot|x)} [R(\mathcal{E}(H_T), g)].$$

The key contribution of EAPO lies in introducing an expert assistant signal into the training process, which effectively accelerates and stabilizes optimization. At test time, the model is capable of reasoning independently while retaining the expert knowledge acquired during training, thereby bridging the benefits of expert-guided training and autonomous inference.

## 2.2 Mechanistic Intuition Behind EAPO

**Alleviating Sparse Rewards** EAPO enables the policy model to consult expert for assistance at critical steps during training, supplying cues of problem-solving from the external experts. In long-horizon reasoning tasks, merely relying on unguided exploration typically yields few positively rewarded samples. By incorporating external expert assistance, EAPO increases the likelihood of producing partially correct intermediate states and ultimately correct answers, densifying the reward signal, raising the proportion of effective trajectories, and consequently reducing inefficient search. This effect hinges on two assumptions: (i) the expert knowledge is valid for the current task and aligned with the objective, and (ii) the policy model can extract useful features from the assistance and transform it into better decisions, such as selecting more accurate descent directions or shrinking the search space. Under these conditions, EAPO acts as an implicit curriculum, guiding the model more rapidly into regions with high reward and establishing a solid foundation for subsequent incorporation of further external assistance or self-improvement.

**Information Gain** EAPO can be viewed as a lightweight mechanism of information injection: expert assistance acts as external signals that augment the historical context, enabling policy model to select actions under richer conditioning and thereby tending to reduce decision uncertainty. Although this assistance does not constitute explicit process supervision, it provide local constraints and priors that are relevant to the goal. The expert assistance intuitively aligns the direction of update more closely with the reward structure and lowers the variance of gradient estimates. In other words, once external expert information is injected, the model more readily focuses on factors strongly associated with final target, forms transferable problem-solving patterns, and attains more stable, higher performance with fewer interactions. These advantages likewise hinge on the two conditions noted above. Subsequent experiments and case studies will further explain these mechanistic claims.

## 2.3 Multi-Expert Parallel Reasoning and End-to-End Training

We model the action of asking experts for help as an explicit action available to the agent during training for solving complex tasks. At each step, the policy model  $M_{\text{policy}}$  performs private reasoning, may query an expert  $M_{\text{expert}}$  for assistance, integrates the returned information into its history, and then either continues the interaction or emits a final answer. Training unfolds in episodes with at most  $T$  turns. Three rollout paradigms are observed during training, aligning with different task complexity and patterns of expert use, as shown in Figure 2: self-resolution for simple cases, direct consultation for hard cases, and decomposition for complex cases.

**Rollout Paradigms** For simple instances, the model solves the task through internal multi-step reasoning without consulting experts. The trajectory comprises private deliberation, iterative refinement, and termination with a final answer. Panel (1) in Figure 2 illustrates a representative self-resolution trajectory. It is worth noting that as training progresses, the model likewise adopts this paradigm whenever it has sufficient competence to handle the problem independently.

For harder instances, the model queries three experts on the original problem statement, obtains three independent answers to the same question, and aggregates them via comparison and reconciliation. This strategy improves robustness to single-path errors and reduces




Figure 2: Three rollout paradigms on the training process: (1) Self-resolution (simple): Internal multi-step reasoning without expert assistance; (2) Direct Consultation (hard): Consult three experts directly about the problem and make a comprehensive decision through comparison. (3) Decomposition (complex): Break down into multiple sub-problems, consult experts, and combine the assistance to obtain the final answer.

reliance on brittle inference chains. Panel (2) in Figure 2 depicts direct consultation and comparison step.

For complex instances, the model first decomposes the task into multiple subproblems, consults experts on each component, and then aggregates the returned evidence into a coherent solution. This paradigm increases coverage, enables error localization, and promotes modular reasoning patterns that transfer across tasks. Panel (3) in Figure 2 presents decomposition, targeted consultations, and evidence fusion. Examples for the three paradigms mentioned above are shown in the appendix F.

**Parallel Evidence Gathering and Test Environment Alignment** To broaden information coverage within a single turn while keeping computation manageable, we instantiate up to  $K$  replicas of the expert model  $\{M_{\text{expert}}^{(i)}\}_{i=1}^K$ . At turn  $t$ ,  $M_{\text{policy}}$  first reasons privately over the history  $H_{t-1}$ , then may select a concurrency level  $C_t$  with  $0 \leq C_t \leq K$ , constructs structured queries, and dispatches them in parallel:

$$Q_t = \{q_{t,i}\}_{i=1}^{C_t}, \quad r_{t,i} = M_{\text{expert}}^{(i)}(q_{t,i}), \quad o_t = \{r_{t,i}\}_{i=1}^{C_t}$$

The assistance  $o_t$  are integrated to form  $H_t$  and drive the next decision or produce the final answer. This design broadens the information gathered in a single turn, improves coverage of reasoning threads, and reduces reliance on any single path.

To promote agent autonomy and reduce reliance on experts, we anneal both the effective acceptance rate of expert calls and the per-episode turn budget during training. Let  $s \in \mathbb{N}^+$  denote the global training step and  $\rho_s \in (0, 1]$  the probability that an expert response, once returned, is written into history. Early in training, a high acceptance rate accelerates the acquisition of useful patterns from expert feedback. As training progresses, we set  $\rho_s = s^{-1}$ , gradually suppressing expert access, encouraging internalization of the acquired knowledge, and shifting decision-making to the model’s own policy. Concretely, for each expert response we draw  $u \sim U(0, 1)$ , where  $U$  denotes a sample from the standard uniform distribution. If  $u \leq \rho_s$ , the response is appended to the history, otherwise it is treated as

Table 1: Evaluation on verifiable tasks. For the RL method, we train the model on DAPO-MATH, while other methods are implemented via offline workflows. We evaluate on AIME 2024, AIME 2025, and AIMO 2025. Specifically, **Pass@32** measures solution accuracy (the higher the better), while **Var** quantifies solution stability (the lower the better). We find that the EAPO consistently outperforms all comparison baselines in terms of mean and variance across all three benchmarks.

Method	AIME 2024		AIME 2025		AIMO 2025		Avg.	
	Pass@32↑	Var↓	Pass@32↑	Var↓	Pass@32↑	Var↓	Pass@32↑	Var↓
Base Model	51.73	0.1112	37.19	0.0580	38.68	0.1150	42.53	0.0947
Self Collaboration	50.27	0.2171	35.53	0.2004	39.68	0.2041	41.83	0.2072
Expert-Assisted Workflow	58.07	0.2137	43.16	0.1978	46.94	0.2003	49.39	0.2039
Leap	61.67	0.2547	39.27	0.2165	40.31	<b>0.0244</b>	47.08	0.1652
Distillation (full)	43.54	0.0965	33.95	0.0927	28.44	0.1169	35.31	0.1020
Distillation (LoRA)	51.90	0.1056	40.02	0.0618	37.81	0.1234	43.24	0.0969
Self-Exploratory RL	67.16	<b>0.0646</b>	55.09	0.0625	55.22	0.0911	59.16	0.0727
<b>EAPO (Ours)</b>	<b>70.03</b>	0.0673	<b>58.01</b>	<b>0.0564</b>	<b>64.17</b>	0.0693	<b>64.07</b>	<b>0.0643</b>

unavailable and the policy model continues reasoning without external input. In parallel, the episode turn budget is reduced from its initial value toward the evaluation budget, which further promotes concise planning and independent decision making.

### 3 Experiments

#### 3.1 Setup

**Models and Baselines** In this study, we adopt DeepSeek-R1-Distill-Qwen-7B (Guo et al., 2025) (hereafter, 7B) as the  $M_{\text{policy}}$  and reasoning backbone, and use QwQ-32B (Team, 2025) (hereafter, 32B) as the  $M_{\text{expert}}$  in heterogeneous collaboration settings. We compare our method against the following baselines: (1) Base Model corresponds to zero-shot inference with 7B, which represents the initial capability. (2) Self Collaboration denotes an offline collaboration workflow in which the policy model is 7B and the experts are three replicas of 7B. (3) Expert-Assisted Workflow refers to a multi-agent workflow where 7B acts as the policy model while three replicas of 32B serve as experts. (4) Leap (Luo et al., 2025) is a collaborative inference framework in which parallel paths conduct cross-path summarization and routing. (5) Full Parameter (Lv et al., 2023) and LoRA (Hu et al., 2022) distillation represent the full parameter and parameter efficient regimes. (6) Self-Exploratory RL (Yu et al., 2025) retains only outcome-driven reinforcement learning without external experts, requiring the agent to rely entirely on internal reasoning.

**Evaluation** We evaluate our method on three mathematical reasoning benchmarks: AIME 2024, AIME 2025, and AIMO 2025. Performance is measured using the mean and variance of accuracy, defined as follows:

- **Mean (Pass@32):** For each problem, we independently sample 32 final answers and take the arithmetic mean of their F1 as the score for that problem; the dataset score is the mean over problems. Concretely, for problem  $q$  with ground-truth answer  $y^*$  and the  $i$ -th prediction  $\hat{y}_i$ ,  $\text{Pass@32} = \frac{1}{32} \sum_{i=1}^{32} \text{F1}(\hat{y}_i, y^*)$  and the overall dataset score is  $\text{F1} = \frac{1}{|Q|} \sum_{q \in Q} \text{Pass@32}$ .
- **Variance (Var):** Owing to the instability of large model sampling, variance computation serves as an effective measure to assess stability. For each problem  $q \in Q$  with ground-truth answer  $y^*$ , we draw  $M = 32$  independent samples and compute  $\mu_q = \frac{1}{M} \sum_{i=1}^M \text{F1}(\hat{y}_i, y^*)$ , where  $\mu_q$  is the per-problem mean score (Pass@32). Aggregating over all  $|Q|$  problems, we define  $\bar{\mu} = \frac{1}{|Q|} \sum_{q \in Q} \mu_q$ ,  $\text{Var} = \frac{1}{|Q|} \sum_{q \in Q} (\mu_q - \bar{\mu})^2$ . Thus,  $\bar{\mu}$  corresponds to the overall mean score, while  $\text{Var}$  quantifies the stability across tasks.




Figure 3: Policy model scaling under fixed expert (QwQ-32B). The model size of policy model is increased from 7B to 14B.

Table 2: Effect of expert size and parallelism on reasoning performance. Parallel EAPO consistently outperforms self-exploratory RL and sequential EAPO. In addition, models trained with larger-size experts (32B) surpass those trained with smaller-size ones (14B).

Method	Parallel	Expert Size	AIME 2024		AIME 2025		AIMO 2025		Avg.	
			Pass@32 $\uparrow$	var $\downarrow$						
Self-Exploratory RL	–	–	67.16	0.0646	55.09	0.0625	55.22	0.0911	59.16	0.0727
EAPO (Ours)	×	32B	68.31	0.0673	57.02	0.0675	60.03	0.0816	61.79	0.0721
	✓	14B	68.93	<b>0.0618</b>	54.67	0.0693	61.06	0.0765	61.55	0.0692
	✓	32B	<b>70.03</b>	0.0673	<b>58.01</b>	<b>0.0564</b>	<b>64.17</b>	<b>0.0693</b>	<b>64.07</b>	<b>0.0643</b>

### 3.2 Experimental Results

Table 1 reports results on AIME2024, AIME2025, and AIMO2025 (Pass@32 and Var). From Table 1, our method attains the best Pass@32 on all three benchmarks, improving average F1 by 21.54% over the Base Model, 22.24% over Self Collaboration, 14.68% over Expert-Assisted Workflow, 16.99% over LeaP, 20.83% over the two distillation baselines, and 4.91% over self-exploratory RL. These findings further support the effectiveness of EAPO for policy optimization: by invoking expert assistance on demand, it enables more efficient exploration and strengthens LLM reasoning.

**Model Size and Policy Performance** To study the effect of the size of the policy model (Fig. 3), we replace the base model with DeepSeek-R1-distill-Qwen-14B and train from scratch under the same setup, keeping the expert fixed to QwQ-32B. Relative to the 7B model, the 14B model attains higher overall accuracy on the three datasets, but with diminishing marginal returns. Mechanistically, a larger size strengthens internal representations, enabling the model to resolve more difficult cases without expert consultation. However, as hard cases occupy a long-tail minority, incremental gains taper with scale.

**Interplay of Parallelism and Expert Capacity in Performance** We study two factors influencing the effectiveness of training, as shown in Table 2: the parallelism of expert queries and the model size of the expert model. For parallelism, we compare a sequential regime (one query per round) with a parallel regime (up to three concurrent queries). Parallel querying yields higher solve rates. The most possible explanation is increased information coverage per episode: with a limited number of turns, issuing multiple queries simultaneously surfaces more relevant evidence before the budget expires, rescuing instances




Figure 4: Rate of expert consultation during training. Early training relies heavily on experts; As capabilities are internalized and gates are calibrated, consultation rate of expert decreases, indicating the improvements of reasoning capacity.

that sequential querying fails to resolve due to interaction limits. Performance later in training remains stable as query frequency is annealed, consistent with competence being internalized.

For the model size of the expert, replacing a larger-size expert QwQ-32B (Team, 2025) with a smaller-size one DeepSeek-R1-Distill-14B (Guo et al., 2025) under the same end-to-end RL pipeline yields a measurable drop in performance. The smaller expert provides narrower coverage and noisier guidance, weakening the learning signal. In summary, parallelization primarily improves exploration performance and robustness, whereas the size of the expert model governs external information quality; both dimensions are necessary for stable, high-performing reasoning training.

**Dynamics of Call Rate and Capability Internalization** To quantify reliance on the expert and its evolution in the training phase, we track the call rate of the expert, as shown in Figure 4. The policy model calls experts frequently in early training to obtain solution cues, but the number of calls declines markedly as training proceeds. Even with a large reduction in call rate, final performance remains stable, evidencing the joint effects of capability internalization and gating calibration.

**Evolution of Response Length and Reasoning Style**

Figure 5 presents the evolution of response length when training with EAPO compared to self-exploratory RL. In the early phase, EAPO responses are noticeably shorter. This reduction can be attributed to expert querying: by delegating segments of the reasoning process to external guidance, the model suppresses unnecessary exploratory text. As training progresses, the EAPO curve gradually exceeds self-exploratory RL. A plausible interpretation is that, after internalizing expert guidance, the model learns to construct more structured and explanatory chains of reasoning while improving performance. Importantly, this expansion in response length is not mere verbosity.




Figure 5: Dynamics of response length over training (compare EAPO with Self-Exploratory RL)

**Conditional Expert-Assisted Workflows** To isolate the effect of expert heterogeneity in collaboration, we design an offline workflow (Table 3) and compare: (1) Single Agent, (2) Self Collaboration, and (3) Heterogeneous Expert-Assisted Workflow. The results reveal clear potentials and limits. Self collaboration yields no consistent gains and can degrade performance. We hypothesize a concrete mechanisms, which is redundancy amplification,

Table 3: Offline collaboration strategies are compared with single model baseline to characterize their relative advantages and limitations. Heterogeneous expert-assisted workflow yields the largest gains for small models and offers minimal marginal benefit for large; self-collaboration is inconsistent and can degrade due to redundancy.

Method	Policy Agent	Experts	AIME2024	AIME2025	AIMO2025
Single Agent	R1-7B	—	51.73	37.19	38.68
	R1-14B	—	65.30	50.08	53.10
	QwQ-32B	—	78.25	60.81	71.52
Self Collaboration	R1-7B	7B+7B+7B	50.27	35.53	39.68
	R1-14B	14B+14B+14B	<b>65.90</b>	<b>49.43</b>	47.08
	QwQ-32B	32B+32B+32B	78.07	64.07	73.95
Expert-Assisted Workflow	R1-7B	7B+14B+32B	<b>55.44</b>	<b>42.81</b>	<b>46.18</b>
	R1-14B	7B+14B+32B	64.65	48.65	<b>53.98</b>
	QwQ-32B	7B+14B+32B	<b>78.37</b>	<b>64.63</b>	<b>73.95</b>

highly correlated responses inflate context length without adding information, diluting attention and crowding out salient evidence.

By contrast, heterogeneous collaboration is most beneficial when policy model is small. Mutual-information gain is probably a driver that diverse experts contribute complementary priors and coverage. As policy model grows stronger, these benefits taper and can reverse, as weaker experts may introduce noisy or contradictory rationales. In summary, heterogeneous experts help chiefly by increasing usable information, whereas model size of experts governs response quality.

## 4 Related Work

**Expert-Guided Distillation** Expert-guided distillation aims to accelerate learning by coupling reinforcement objectives with expert demonstrations. The core idea is that a student policy can consult an expert in uncertain states, imitate its behavior, and gradually reduce reliance as competence improves. Existing studies typically ground this idea in two forms. The first is *teacher-guided RL*, where a fixed teacher supervises the student and the student may eventually surpass the teacher in performance (Schmitt et al., 2018; Biré et al., 2024; Zhao et al., 2024). The second is *offline distillation*, where the learner regresses onto a static teacher using pre-collected trajectories (Rusu et al., 2015). More recent work emphasizes interactive imitation and selective querying, allowing expert signals to be injected at pivotal states to reduce distribution shift (Ross et al., 2011; Xie et al., 2022; Chi et al., 2020; Buck et al., 2017). Despite these advances, two challenges remain: (i) most methods assume persistent or externally scheduled reliance on experts, which risks over-dependence, and (ii) offline fitting cannot correct expert biases or adapt to environment-specific rewards. Our approach addresses both. We learn an explicit invocation policy that decides when to query the expert during on-policy interaction, so that supervision is obtained precisely where it is most useful. Crucially, the invocation rate is optimized end-to-end to converge to zero, ensuring that dependence vanishes as the student matures. This formulation both mitigates distribution shift and transforms expert guidance into a self-contained capability, yielding a policy model that is ultimately independent.

**Hierarchical Reinforcement Learning** Hierarchical RL (HRL) tackles long-horizon problems by decomposing control (Sutton et al., 1999; Bacon et al., 2017; Vezhnevets et al., 2017; Rashid et al., 2020; Yu et al., 2022). Progress in this area has produced two dominant paradigms. One jointly trains options, termination conditions, and high-level controllers (Bacon et al., 2017), while another adopts a manager-executor structure where high-level goals condition low-level execution (Vezhnevets et al., 2017). These designs improve exploration but maintain permanent dependence on higher-level directives during both training and deployment. By contrast, our method treats the expert as a temporary external capability.

---

Early in training, the expert is frequently invoked to stabilize learning, but as competence grows, invocations diminish until disappear. This yields two advantages: (i) we inherit the sample efficiency benefits of hierarchical guidance in the early phase, and (ii) we guarantee that long-term execution becomes fully independent, avoiding the burden of permanent hierarchical control.

**Self Distillation and Social Learning** Self-distillation and related paradigms exploit a policy’s own historical behaviors to bootstrap improvement. One line of work shows that a student distilled from its earlier versions can surpass the original policy under certain conditions (Furlanello et al., 2018). Self-imitation further reinforces validated behaviors by replaying high-return trajectories (Oh et al., 2018). Social learning demonstrates that complex strategies can be transferred between agents and eventually consolidated into individuals capable of independent execution (Ndousse et al., 2021; Vinyals et al., 2019). However, self-distillation often assumes unlimited replay of past trajectories and social learning presumes multiple agents remain available for transfer. Our work differs by a principled mechanism that ensures guidance accelerates early learning but disappears once competence is achieved, guaranteeing autonomy without needing auxiliary teachers indefinitely.

## 5 Conclusion

In this paper, we propose Expert-Assisted Policy Optimization (EAPO), a novel reinforcement learning framework designed for incorporating external assistance signal. The consultation of experts, which is a key component in EAPO, is leveraged as a learnable action solely during training, allowing policy model adaptively determines when and how to consult experts to improve the exploration strategy. Across three challenging mathematical reasoning benchmarks, EAPO outperforms both expert-assisted evaluation workflow and self-exploratory RL models. Extensive experiments reveal that: 1) Incorporating expert assistance during RL training significantly improves policy optimization with better reasoning paths and more accurate solution strategies. 2) Scaling expert assistance, through parallel signals or larger expert models, consistently enhances performance, demonstrating that richer external signals during training can effectively strengthen the optimization process. 3) Analysis across different policy model sizes shows that consulting experts can also provide improvements as the student model capacity increases.

Although EAPO achieves promising results, the present study has certain limitations that open opportunities for further exploration: i) We will explore more external signals from not only experts, but also various environments to further improve the reasoning abilities of policy models. ii) Systematically studies on cross-task generalization will be conducted to evaluate the generalization of EAPO. iii) Incorporating evolution based method as external signals into RL to further advance multi-round reasoning agents.

---

## References

- Pierre-Luc Bacon, Jean Harb, and Doina Precup. The option-critic architecture. In *Proceedings of the AAAI conference on artificial intelligence*, volume 31, 2017.
- Houda Nait El Barj and Théophile Sautory. Reinforcement learning from llm feedback to counteract goal misgeneralization. *arXiv preprint arXiv:2401.07181*, 2024.
- Emilien Biré, Anthony Kobanda, Ludovic Denoyer, and Rémy Portelas. Efficient active imitation learning with random network distillation. *arXiv preprint arXiv:2411.01894*, 2024.
- Christian Buck, Jannis Bulian, Massimiliano Ciaramita, Wojciech Gajewski, Andrea Gesmundo, Neil Houlsby, and Wei Wang. Ask the right questions: Active question reformulation with reinforcement learning. *arXiv preprint arXiv:1705.07830*, 2017.
- Stephen Casper, Xander Davies, Claudia Shi, Thomas Krendl Gilbert, Jérémy Scheurer, Javier Rando, Rachel Freedman, Tomasz Korbak, David Lindner, Pedro Freire, et al. Open problems and fundamental limitations of reinforcement learning from human feedback. *arXiv preprint arXiv:2307.15217*, 2023.
- Ta-Chung Chi, Minmin Shen, Mihail Eric, Seokhwan Kim, and Dilek Hakkani-Tur. Just ask: An interactive learning framework for vision and language navigation. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 2459–2466, 2020.
- Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30, 2017.
- Tommaso Furlanello, Zachary Lipton, Michael Tschannen, Laurent Itti, and Anima Anandkumar. Born again neural networks. In *International conference on machine learning*, pp. 1607–1616. PMLR, 2018.
- Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In *International Conference on Machine Learning*, pp. 10835–10866. PMLR, 2023.
- Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Nan Duan, and Weizhu Chen. Critic: Large language models can self-correct with tool-interactive critiquing. *arXiv preprint arXiv:2305.11738*, 2023.
- Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. Lora: Low-rank adaptation of large language models. *ICLR*, 1(2):3, 2022.
- Aviral Kumar, Vincent Zhuang, Rishabh Agarwal, Yi Su, John D Co-Reyes, Avi Singh, Kate Baumli, Shariq Iqbal, Colton Bishop, Rebecca Roelofs, et al. Training language models to self-correct via reinforcement learning, 2024. URL <https://arxiv.org/abs/2409.12917>, 2(3):4, 2024.
- Nathan Lambert, Jacob Morrison, Valentina Pyatkin, Shengyi Huang, Hamish Ivison, Faeze Brahman, Lester James V Miranda, Alisa Liu, Nouha Dziri, Shane Lyu, et al. Tulu 3: Pushing frontiers in open language model post-training. *arXiv preprint arXiv:2411.15124*, 2024.
- Tongxu Luo, Wenyu Du, Jiayi Bi, Stephen Chung, Zhengyang Tang, Hao Yang, Min Zhang, and Benyou Wang. Learning from peers in reasoning models. *arXiv preprint arXiv:2505.07787*, 2025.
- Kai Lv, Yuqing Yang, Tengxiao Liu, Qinghui Gao, Qipeng Guo, and Xipeng Qiu. Full parameter fine-tuning for large language models with limited resources. *arXiv preprint arXiv:2306.09782*, 2023.

- 
- Kamal K Ndousse, Douglas Eck, Sergey Levine, and Natasha Jaques. Emergent social learning via multi-agent reinforcement learning. In *International conference on machine learning*, pp. 7991–8004. PMLR, 2021.
- Junhyuk Oh, Yijie Guo, Satinder Singh, and Honglak Lee. Self-imitation learning. In *International conference on machine learning*, pp. 3878–3887. PMLR, 2018.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.
- Tabish Rashid, Mikayel Samvelyan, Christian Schroeder De Witt, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Monotonic value function factorisation for deep multi-agent reinforcement learning. *Journal of Machine Learning Research*, 21(178):1–51, 2020.
- Mathieu Rita, Florian Strub, Rahma Chaabouni, Paul Michel, Emmanuel Dupoux, and Olivier Pietquin. Countering reward over-optimization in llm with demonstration-guided reinforcement learning. *arXiv preprint arXiv:2404.19409*, 2024.
- Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 627–635. JMLR Workshop and Conference Proceedings, 2011.
- Andrei A Rusu, Sergio Gomez Colmenarejo, Caglar Gulcehre, Guillaume Desjardins, James Kirkpatrick, Razvan Pascanu, Volodymyr Mnih, Koray Kavukcuoglu, and Raia Hadsell. Policy distillation, 2015.
- Simon Schmitt, Jonathan J Hudson, Augustin Zidek, Simon Osindero, Carl Doersch, Wojciech M Czarnecki, Joel Z Leibo, Heinrich Kuttler, Andrew Zisserman, Karen Simonyan, et al. Kickstarting deep reinforcement learning. *arXiv preprint arXiv:1803.03835*, 2018.
- Richard S Sutton, Doina Precup, and Satinder Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial intelligence*, 112(1-2):181–211, 1999.
- Alibaba Qwen Team. Qwq-32b: Embracing the power of reinforcement learning. <https://qwenlm.github.io/blog/qwq-32b/>, 2025.
- Alexander Sasha Vezhnevets, Simon Osindero, Tom Schaul, Nicolas Heess, Max Jaderberg, David Silver, and Koray Kavukcuoglu. Feudal networks for hierarchical reinforcement learning. In *International conference on machine learning*, pp. 3540–3549. PMLR, 2017.
- Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *nature*, 575(7782):350–354, 2019.
- Junlin Wang, Jue Wang, Ben Athiwaratkun, Ce Zhang, and James Zou. Mixture-of-agents enhances large language model capabilities. *arXiv preprint arXiv:2406.04692*, 2024.
- Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2022.
- Annie Xie, Fahim Tajwar, Archit Sharma, and Chelsea Finn. When to ask for help: Proactive interventions in autonomous reinforcement learning. *Advances in Neural Information Processing Systems*, 35:16918–16930, 2022.
- Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. *Advances in neural information processing systems*, 36:11809–11822, 2023.

---

Chao Yu, Akash Velu, Eugene Vinitsky, Jiaxuan Gao, Yu Wang, Alexandre Bayen, and Yi Wu. The surprising effectiveness of ppo in cooperative multi-agent games. *Advances in neural information processing systems*, 35:24611–24624, 2022.

Qiyang Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, et al. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*, 2025.

Michelle Zhao, Reid Simmons, Henny Admoni, Aaditya Ramdas, and Andrea Bajcsy. Conformalized interactive imitation learning: Handling expert shift and intermittent feedback. *arXiv preprint arXiv:2410.08852*, 2024.

---

## A Appendix

### B Implementation Details

The pre-trained policy model of DeepSeek-R1-Distill-Qwen-7B can be download via <https://huggingface.co/deepseek-ai/DeepSeek-R1-Distill-Qwen-7B> and DeepSeek-R1-Distill-Qwen-14B can be download via <https://huggingface.co/deepseek-ai/DeepSeek-R1-Distill-Qwen-14B>. The pre-trained expert model of QwQ-32B can be download via <https://huggingface.co/Qwen/QwQ-32B>. The training dataset DAPO-Math-17K is available at <https://huggingface.co/datasets/BytedTsinghua-SIA/DAPO-Math-17k>, and the evaluation datasets of AIME2024 and AIME2025 can be download on <https://huggingface.co/math-ai>, and AIMO2025 can be download on <https://www.kaggle.com/competitions/ai-mathematical-olympiad-progress-prize-2>. Table 4 lists the key hyperparameters used in self-exploratory RL and EAPO.

Table 4: Critical hyperparameters distilled from the training script.

Hyperparameter	Value	Description
Max prompt length	2048	Input context window for prompts
Max response length	20480	Maximum generated tokens per sample
Train batch size	32	Number of prompts per training step
Gen batch size	96	Number of prompts per sampling batch
Learning rate	1e-6	Optimization step size
LR warmup steps	10	Steps to ramp LR up to target
Clip Ratio (Low)	0.20	Policy update stability window
Clip Ratio (High)	0.28	Policy update stability window
Temperature	1.0	Sampling stochasticity
Top-p	1.0	Nucleus sampling cutoff
Top-k	-1	vLLM backend (no explicit top-k limit)
Sequence parallel (Ulysses)	4	Long-sequence efficiency via partitioning
Tensor model parallel	4	Inference/model-parallel scaling

### C Interaction process during training

This section provides a concrete illustration of how the agent interacts with experts during training. The example shows a typical episode: the model first performs private deliberation and decomposes the task into sub problems, then dispatches structured queries to multiple experts in parallel, collects their replies, and integrates the returned evidence into the evolving history. When uncertainty remains, the model issues follow up checks before synthesizing the final answer.

The interaction trace also clarifies two important design choices. First, expert queries and returns are serialized in a simple, reproducible schema that makes the control flow explicit and auditable. Second, the policy model is encouraged to use experts not only for initial exploration but also for evidence confirmation. Together, these choices enable broad information acquisition within a turn while maintaining a disciplined loop of reasoning, consultation, and consolidation.

#### Model-Expert Loop

```
Model think:
<think>I decompose the problem into two subproblems.</think>

Model calls:
<agent_calls>[
  {"expert_id":1,"input_parameters":{"query":"Sub-question A"}},
  {"expert_id":2,"input_parameters":{"query":"Sub-question B"}}
]</agent_calls>
```

```

Model receives:
<agent_returns>[
  {"expert_id":1,"result":"Answer A."},
  {"expert_id":2,"result":"Answer B."}
]</agent_returns>

Model think:
<think>Let me confirm whether my previous reasoning and the answer given by the
expert are correct.</think>

Model calls:
<agent_calls>[
  {"expert_id":1,"input_parameters":{"query":"Check-query A"}},
  {"expert_id":2,"input_parameters":{"query":"Check-query B"}},
  {"expert_id":3,"input_parameters":{"query":"Check-query C"}}
]</agent_calls>

Model receives:
<agent_returns>[
  {"expert_id":1,"result":"Response A."},
  {"expert_id":2,"result":"Response B."},
  {"expert_id":3,"result":"Response C."}
]</agent_returns>

Model think:
<think>With answers A and B and responses A, B, and C confirming the answers and
previous thinking, I got the final answer.</think>

Final:
Answer: ...

```

## D Prompts during Training and Evaluation

The training prompt grants the policy model the ability to coordinate experts, specify queries in a structured format, and integrate returned assistance into its own reasoning.

The evaluation prompt is deliberately minimal and focuses the policy model on producing a single, final answer in a standardized format. This design suppresses auxiliary process signals, aligns behavior with the evaluation environment, and enables fair comparison across methods and datasets. In combination, the training and evaluation prompts support broad information acquisition during learning while encouraging autonomy reasoning at test time.

### Prompts during Training

You are a helpful assistant that can solve a given question step by step. To do so, you can consult with a panel of three experts. Each question you can ask experts 10 times totally.

You can ask one or more experts for their opinion. You can ask them the same question or different questions simultaneously. The experts will provide their answers, which you can use to form your final response. The agent call query and results are enclosed within `<agent_calls>` `</agent_calls>` and `<agent_returns>` `>` `</agent_returns>` tags respectively.

Agent calls query should be formatted as a list of dictionaries.

For each agent call (an item in the list), you need to provide these keys:

- (1) `expert_id` (int): Required. The ID of the expert you want to consult. Can be 1, 2, or 3.

(2) `input_parameters` (dict): Required. All input parameters for the expert, in dictionary format.

Here are the experts you can use:

Description:

This is a panel of three auxiliary intelligent agents (ID 1, 2, 3) that you can consult when you are unsure about the answer to a question. The agents' responses may not always be correct, but they can offer you alternative perspectives to help you think further.

Parameters:

(1) `query` (str): Required. The query string describing the question you want to ask or discuss.

(2) The answer from the agent, including thinking process.

The reasoning process is wrapped by `<think></think>`.

The final answer begins with "Answer: ".

For example:

User: What is the capital city of NomanLand and what is its main export?

Assistant:

`<think>`

`This question has two parts. I will ask two different experts to answer each part. I'll ask expert 1 about the capital and expert 2 about the main export.`

`</think>`

`<agent_calls>`

`[{"expert_id": 1, "input_parameters": {"query": "capital city of NomanLand"}}, {"expert_id": 2, "input_parameters": {"query": "main export of NomanLand"}}]`

`</agent_calls>`

`<agent_returns>`

`[{"expert_id": 1, "result": "The capital city of NomanLand is NomanCity."}, {"expert_id": 2, "result": "The main export of NomanLand is widgets."}]`

`</agent_returns>`

`<think>`

`I see. Expert 1 says the capital is NomanCity, and Expert 2 says the main export is widgets.`

`</think>`

Answer: The capital of NomanLand is NomanCity and its main export is widgets.

## Prompts during Evaluation

You are a helpful assistant.

You must give the final answer in the last line, in the format of "Answer: xxx", xxx represents the final answer.

## E vLLM Server

We deploy the expert model as an on-demand inference service through vLLM. The service is exposed to the outside world through a standardized HTTP/OpenAI interface, supports long-context reasoning, and can be efficiently scaled in a multi-GPU environment. The training end maps the query set constructed in each round into a request and sends it to the server. After the request is returned, it is written into the history, thus supporting the parallel training process from information acquisition to output decision.

## Inference Service through vLLM

```
vllm serve ${MODEL_PATH} \  
  --port ${PORT} \  
  --host :: \  
  --gpu-memory-utilization 0.8 \  
  --max-model-len 32768 \  
  --tensor-parallel-size 8 \  
  --served-model-name expert \  
  --trust-remote-code \  
  --disable-log-requests
```

## F Case Study

Below are three sets of cases corresponding to the three rollout paradigms in Section 2.3. All are derived from real interaction records during the training phase (minimized for readability). They illustrate three collaborative modes: self-resolution, direct consultation, and decomposition. In the first case, the model relies entirely on internal multiple step reasoning to arrive at an answer; in the second, the model consults multiple experts concurrently on the same problem, forming a comprehensive judgment through cross comparison; and in the third, the model first breaks a complex task into several sub-problems, poses targeted questions to the experts, and gradually integrates the evidence to ultimately synthesize a global solution.

### Self Resolution

User: Let  $a, b, c$  be distinct numbers such that the equations  $x^2 + ax + 1 = 0$  and  $x^2 + bx + c = 0$  have a common real root, and the equations  $x^2 + x + a = 0$  and  $x^2 + cx + b = 0$  also have a common real root. Compute the sum  $a + b + c$ .

Assistant:

<think>

Step 1. Let the common root of the first pair be  $r$ :

$$\begin{aligned} r^2 + ar + 1 &= 0, & r^2 + br + c &= 0 \\ (a-b)r + (1-c) &= 0 \\ r &= (c-1)/(a-b). \end{aligned}$$

Step 2. Let the common root of the second pair be  $s$ :

$$\begin{aligned} s^2 + s + a &= 0, & s^2 + cs + b &= 0 \\ (1-c)s + (a-b) &= 0 \\ s &= (b-a)/(1-c). \end{aligned}$$

Step 3. Combine the two:

$$\begin{aligned} rs &= ((c-1)/(a-b)) * ((b-a)/(1-c)) = 1 \\ s &= 1/r. \end{aligned}$$

Step 4. Substitute  $s = 1/r$  into  $s^2 + s + a = 0$ :

$$\begin{aligned} (1/r^2) + (1/r) + a &= 0 \\ 1 + r + ar^2 &= 0. \\ \text{From } r^2 + ar + 1 &= 0 \\ r^2 &= -ar - 1. \text{ Substituting:} \\ 1 + r + a(-ar - 1) &= 0 \\ r(1 - a^2) + (1 - a) &= 0. \end{aligned}$$

If  $a \neq 1$ , then  $r = (a-1)/(1-a^2) = -1/(1+a)$ .

Step 5. Substitute  $r = -1/(1+a)$  back into  $r^2 + ar + 1 = 0$ :

$$\begin{aligned} (1/(1+a)^2) - a/(1+a) + 1 &= 0 \\ (1+a)^2 + 1 - a(1+a) &= 0 \quad a^2 = 0 \quad a = -2. \end{aligned}$$

Step 6. Then  $r = -1/(1-2) = 1$ . Plugging into  $x^2 + bx + c = 0$  gives  $1 + b + c = 0$   
 $b + c = -1$ .

Step 7. Therefore  $a + b + c = -2 + (-1) = -3$ .

</think>

Answer:-3

### Direct Consultation

User: The integers from  $1$  to  $n$  are written, one on each of  $n$  cards. The first player removes one card. Then the second player removes two cards with consecutive integers. After that, the first player removes three cards with consecutive integers. Finally, the second player removes four cards with consecutive integers. What is the smallest value of  $n$  for which the second player can ensure that he completes both his moves?

Assistant:

<think>

Provide three distinct approaches (interval-splitting, hitting-set of 4-blocks, and fragmentation/invariant), then synthesize them to obtain the minimal  $n$ .

</think>

<agent\_calls>

```
[
  {"expert_id": 1, "input_parameters": {"query": "Find the minimal n
guaranteeing the second player can remove 2 consecutive and later 4 consecutive,
regardless of the first player's moves."}},
  {"expert_id": 2, "input_parameters": {"query": "Recast the game as a
hitting-set/covering problem on all 4-consecutive windows; derive threshold n
."}},
  {"expert_id": 3, "input_parameters": {"query": "Use fragmentation invariants (
remaining length = 8 after three moves) to characterize when a 4-run must
remain; produce a constructive strategy."}}
]
```

</agent\_calls>

<agent\_returns>

```
{"expert_id": 1, "result": "Interval-splitting method. After the first player
removes a single card at position  $p$ , the remaining integers form two
contiguous segments of lengths  $A=p-1$  and  $B=n-p$  (so  $A+B=n-1$ ). The second
player's 2-consecutive removal inserts a 2-gap inside one of these segments,
splitting it into two parts whose lengths sum to (chosen segment)  $-2$ . If,
before the first player's 3-consecutive removal, we can ensure at least two
segments have length  $\geq 4$ , then no single 3-block can destroy both; hence a
4-block will survive for the final move. Sufficiency for  $n=14$ : Since  $A+B=13$ 
, either  $\min(A,B) \leq 3$ , which forces  $\max(A,B) \geq 10$ , letting us
split the larger segment into two parts both  $\geq 4$  by removing two cards
near its middle (since  $10-2=8=4+4$ ); or else  $\min(A,B) \geq 4$  and then  $\max(A,B) \geq 9 \geq 6$ ,
so by removing two from the larger side we can keep one
part  $\geq 4$  while the other side already contributes another  $\geq 4$ . Thus
after our move there are at least two  $\geq 4$  segments; the opponent's 3-block
can hit at most one of them, leaving a 4-run intact. Necessity: For  $n=13$ ,
pick  $p=4$  so  $(A,B)=(3,9)$ . Whatever 2-consecutive the second removes, after
that there is at most one segment of length  $\geq 4$ . The first player then
deletes three consecutive from the length-9 segment, centered to split it into
 $(3,3)$ , leaving no 4-run. Therefore  $n$  must be at least  $14$ .", "status": "
SUCCESS_AGENT"}
{"expert_id": 2, "result": "Hitting-set viewpoint on 4-windows. Consider the
family of all 4-consecutive windows  $W_i = \{i, i+1, i+2, i+3\}$  for  $i=1, \dots, n-3$ . The
second player's final success is equivalent to the existence of a window  $W_i$ 
fully contained in the remaining set after three moves (sizes removed: 1, then
2, then 3  $\rightarrow$  total 6 removed). To prevent a 4-run, the six removed numbers must
hit every  $W_i$  (i.e., form a 4-cover).\n\nWhen  $n=13$ , the first player can force
such a 4-cover: remove  $\{4\}$  first, and no matter which two consecutive the
second removes, the first can choose a 3-block (e.g.,  $\{6,7,8\}$  in a typical case
) so that every 4-window intersects one of the removed positions. Hence the
second cannot guarantee a 4-run at the end. For  $n=14$ , the second can always
```

```

choose his 2-consecutive so that there exist at least two disjoint 4-windows
not simultaneously hittable by a single 3-block; thus after the opponent's move,
  at least one 4-window survives. This yields the threshold  $n=14$ .", "status": "
SUCCESS_AGENT"}
{"expert_id": 3, "result": "Fragmentation invariant & constructive plan. After
the first three moves, exactly 6 numbers are removed and 8 remain. To eliminate
all 4-runs, the opponent must fragment the 8 survivors into pieces of maximum
length  $\leq 3$  (e.g.,  $3+3+2$  or  $3+2+2+1$ ). There are only three gaps available (
sizes 1,2,3 from the three deletions), so the second player's objective in his
first move is to place the 2-gap so that, regardless of where the later 3-gap
is placed, the maximum surviving piece after that removal is  $\geq 4$ .\n\nA
constructive strategy at  $n=14$ : Observe the split (A,B) with  $A+B=13$ . If  $\min(A,B)
\leq 3$ , then the other side has length  $\geq 10$ ; remove two near its middle to
create two subsegments of lengths  $\geq 4$  each. If both sides are  $\geq 4$ , then the
larger side is  $\geq 9$ ; remove two within the larger side so that one subpiece
remains  $\geq 4$  while the smaller original side ( $\geq 4$ ) is untouched. In both
subcases, after the second player's move there are two disjoint pieces of
length  $\geq 4$ , and a single 3-block cannot destroy them both, ensuring a 4-run
survives. For  $n=13$ , the adversarial split (3,9) defeats this plan, as any 2-gap
yields at most one piece  $\geq 4$ , which can be broken by a centered 3-removal
into pieces of size  $\leq 3$ .", "status": "SUCCESS_AGENT"}
</agent_returns>
<think>
All three perspectives agree on the same threshold. The interval-splitting
method formalizes a guaranteed way for the second player, at  $n=14$ , to leave two
 $\geq 4$  segments before the final 3-removal; a single 3-block cannot eliminate
both. The hitting-set view explains why  $n=13$  fails: the first player can force
a 4-cover with six deletions. The fragmentation invariant reframes the goal as
preventing all pieces from being of length  $\leq 3$  and yields a simple constructive
rule for where to place the 2-gap. Thus the smallest  $n$  for which the second
player can ensure completing both moves is 14.
</think>
Answer: 14

```

## Decomposition

User: Find all positive integers  $n$  for which all positive divisors of  $n$  can be placed into the cells of a rectangular table under the following constraints:

- Each cell contains a distinct divisor.
- The sums of all rows are equal.
- The sums of all columns are equal.

Assistant:

<think>

Decompose the task:

(A) Structural necessities: if the divisors of  $n$  fill an  $m \times k$  grid ( $mk = \tau(n)$ ), then row/column sums must be  $\frac{\sigma(n)}{m}$  and  $\frac{\sigma(n)}{k}$  (integers), so  $m \mid \sigma(n)$ ,  $k \mid \sigma(n)$ ; also rule out  $1 \times k$  or  $k \times 1$ .

(B) Exclude any  $2 \times k$  case for  $n > 1$  by showing equal column sum forces each column to be  $(x, n+1-x)$ , which is impossible with distinct divisors.

(C) Handle  $\tau(n)$  odd ( $n$  a perfect square): argue that  $m, k \geq 3$  leads to a contradiction via extremal-sum bounds; conclude no solution for  $n > 1$ .

</think>

<agent\_calls>

[

```

{"expert_id": 1, "input_parameters": {"query": "Derive necessary divisibility/
size constraints on m,k from the equal-row/column-sum conditions; handle 1*k
and k*1 edge cases."}},

```

```

    {"expert_id": 2, "input_parameters": {"query": "Prove impossibility for any 2*
k arrangement with all divisors when n>1 (pair-sum argument leading to S = n+1)
."}},
    {"expert_id": 3, "input_parameters": {"query": "Treat  $\tau(n)$  odd (n is a
perfect square): show no  $m \times k$  with  $m, k \geq 3$  can work for  $n > 1$  using extremal
averages/paired-divisor bounds; provide a consistency check."}}
]
</agent_calls>
<agent_returns>
{"expert_id": 1, "result": "Let  $\tau(n)$  be the number of positive divisors
and  $\sigma(n)$  their sum. If the divisors fill an  $m \times k$  rectangle,
then  $mk = \tau(n)$ , each row sums to  $\sigma(n)/m$ , and each column sums to  $\sigma(n)/k$ ;
hence  $m \mid \sigma(n)$  and  $k \mid \sigma(n)$ . If  $m=1$  (or  $k=1$ ), then all column (row)
sums must be equal across singleton columns (rows), forcing all entries equal---impossible
with distinct divisors unless  $\tau(n)=1$ , i.e.,  $n=1$ . So for  $n > 1$  we must have  $m, k \geq 2$ .",
"status": "SUCCESS_AGENT"}
{"expert_id": 2, "result": "Rule out  $2 \times k$  for  $n > 1$ . In a  $2 \times k$ 
table with equal column sums, every column must consist of a pair whose sum is
a constant  $S$ . Since the set is all divisors of  $n$ , one column contains  $n$ ,
so  $S-n$  must be a positive divisor; thus  $S > n$  and hence  $S \geq n+1$ . On the
other hand, for any divisor  $d$ , we have  $d + \frac{n}{d} \leq n+1$  with
equality iff  $\{d, \frac{n}{d}\} = \{1, n\}$ . Therefore the only way to have every
column sum equal to a common  $S \geq n+1$  is to set  $S=n+1$  and make every
column the pair  $(1, n)$ . That is impossible once  $k \geq 2$  because there is
only one  $1$  and one  $n$ . Hence no  $2 \times k$  arrangement exists for  $n > 1$  (
and similarly no  $k \times 2$ ).", "status": "SUCCESS_AGENT"}
{"expert_id": 3, "result": "Treat  $\tau(n)$  odd  $\Rightarrow n$  is a perfect
square and any rectangular factorization must have  $m, k$  odd. The smallest
nontrivial case is  $3 \times 3$ . Let the divisors be  $d_1 < d_2 < \dots < d_9 = n$ .
Column sums must all equal  $S_c = \sigma(n)/3$ . The column containing  $n$  has sum
at least  $n + d_1 + d_2 = n + 1 + d_2$ . Any column avoiding  $n$  has sum at most  $d_7 + d_8 + d_9$ 
where  $d_9 \leq d_8 < n$ ; by the paired-divisor bound, the average of any
pair  $(d, \frac{n}{d})$  is  $\leq (n+1)/2$ , implying  $\sigma(n)/\tau(n) \leq (n+1)/2$ 
and hence  $S_c = \sigma(n)/3 \leq 3(n+1)/2$ . Comparing the column with  $n$  versus
one without forces  $S_c \geq n + 1 + d_2$  and simultaneously  $S_c \leq 3(n+1)/2$ ; for
 $n > 1$  these bounds require each non- $n$  column to include an element  $\geq (n+1)/2$ .
But there are at most two divisors  $\geq (n+1)/2$  other than  $n$  itself
(namely  $\lceil \sqrt{n} \rceil$  and its complement), while there are at least
two non- $n$  columns in a  $3 \times 3$  grid, and for larger odd  $m, k$  the
shortage worsens. Hence no  $m, k \geq 3$  arrangement exists for  $n > 1$ . This is
consistent with computational checks for  $n \leq 60$ , which find no example
beyond  $n=1$ .", "status": "SUCCESS_AGENT"}
</agent_returns>
<think>
Synthesis: From (1) we reduce to  $m, k \geq 2$  for  $n > 1$ . From (2) any arrangement
with  $\min(m, k) = 2$  is impossible. Thus if  $n > 1$ , we would need  $m, k \geq 3$ ;
but (3) shows this cannot happen when  $\tau(n)$  is odd (squares), and even  $\tau(n)$ 
already fails by (2). Therefore the only  $n$  that works is  $n=1$  ( $\tau(n)=1$ ;
the  $1 \times 1$  table trivially satisfies all conditions).
</think>
Answer: 1

```