

MULTIMODAL ITERATIVE RAG FOR KNOWLEDGE VISUAL QUESTION ANSWERING

Changin Choi^{1,3}, Wonseok Lee¹, Jungmin Ko¹, Wonjong Rhee^{1,2}

¹Interdisciplinary Program in Artificial Intelligence

²Department of Intelligence and Information, Republic of Korea, Seoul National University

³Samsung Electronics Co., Ltd, Suwon, Republic of Korea

{ci2015.choi, dnjstjr1017, jungminko, wrhee}@snu.ac.kr

ABSTRACT

While Multimodal Large Language Models (MLLMs) have significantly advanced multimodal understanding, their performance remains limited on knowledge-intensive visual questions that require external knowledge beyond the image. Retrieval-Augmented Generation (RAG) has become a promising solution for providing models with external knowledge, its conventional single-pass framework often fails to gather sufficient knowledge. To overcome this limitation, we propose MI-RAG, a Multimodal Iterative RAG framework that leverages reasoning to enhance retrieval and update reasoning over newly retrieved knowledge across modalities. At each iteration, MI-RAG leverages an accumulated reasoning record to dynamically formulate a multi-query. These queries then drive a joint search across heterogeneous knowledge bases containing both visually-grounded and textual knowledge. The newly acquired knowledge is synthesized into the reasoning record, progressively refining understanding across iterations. Experiments on challenging benchmarks, including Encyclopedic VQA, InfoSeek, and OK-VQA, show that MI-RAG significantly improves both retrieval recall and answer accuracy, establishing a scalable approach in knowledge-intensive VQA.

1 INTRODUCTION

The emergence of Multimodal Large Language Models (MLLMs) has driven significant progress in multimodal understanding and reasoning. Nonetheless, their performance remains constrained in knowledge-intensive Visual Question Answering (VQA) tasks, which require external knowledge beyond the visual content in the image. Answering such questions is particularly challenging as it involves: (1) grounding visual entities in the image to the textual question, (2) collecting text knowledge relevant to both the entities and the question, and (3) synthesizing the visual entities and corresponding textual knowledge to derive the answer.

To address this challenge, multimodal Retrieval-Augmented Generation (RAG) has emerged as a promising solution. The conventional *retrieve-then-read* process starts with a retriever using the input image and question to find relevant image-text pairs from a knowledge base (KB). A reader model then synthesizes this information to create the final answer. Research on optimizing this single-step process has largely advanced along two fronts: improving initial retrieval with high-quality embeddings Lin et al. (2024); Wei et al. (2024); Jiang et al. (2025); Lin et al. (2025); Jiang et al. (2024b); Zhang et al. (2024b), and refining retrieval results by selection and reranking Cocchi et al. (2025); Zhang et al. (2024a); Ling et al. (2025); Chen et al. (2024); Liu et al. (2024b); Yan & Xie (2024); Yang et al. (2025).

Although prior work has achieved notable improvements within the *retrieve-then-read* process, the process itself has inherent limitations for knowledge-intensive VQA. A single retrieval step with an initial query is often insufficient, as imperfect retrievers may fail to gather all necessary knowledge at once Shi et al. (2023); Zhang et al. (2023); Cuconasu et al. (2024). Furthermore, a single reasoning step to ground visual entities and synthesize knowledge is problematic, as distracting or irrelevant content can mislead synthesis and influence the final answer Petroni et al. (2020); Wu et al. (2024); Amiraz et al. (2025); Huang et al. (2025); Wu et al. (2025).




Figure 1: n overview of MI-RAG. Unlike the *retrieve-then-read* process of conventional multimodal RAG, MI-RAG iteratively refines its reasoning and retrieval using a multi-query search over heterogeneous KBs.

verse knowledge by exploring multiple facets of a visually grounded entity and its related textual knowledge across modalities, and (ii) it demands compositional reasoning to synthesize the visual entity with its corresponding knowledge by integrating a diverse set of visual-to-visual, visual-to-text, and text-to-text factual links. This highlights the need for a more specialized approach that can effectively handle the complexities of both visual and textual knowledge.

In response to these multimodal domain considerations, we propose Multimodal Iterative Retrieval-Augmented Generation (MI-RAG). As illustrated in Figure 1, MI-RAG is an iterative framework that cyclically refines its query and reasoning by alternately performing reasoning-guided query transformation and retrieval-augmented reasoning. Our framework makes two primary contributions. First, we employ a reasoning-guided multi-query that dynamically searches multiple facets across modalities. Second, these queries drive a joint search across heterogeneous KBs to find a diverse set of factual links, allowing MI-RAG to compose visually-grounded knowledge and related textual knowledge. Through the synergy of multi-query and heterogeneous KBs, MI-RAG is able to retrieve sufficient knowledge and enable robust compositional reasoning over diverse knowledge across modalities. Through iterations, MI-RAG collects diverse knowledge progressively with accumulating a reasoning record, where each record is the result of compositional reasoning over newly retrieved knowledge, thereby refining the model’s understanding to guide the subsequent iteration step.

2 RELATED WORK

2.1 MULTIMODAL RAG FOR KNOWLEDGE VQA

The dominant paradigm for multimodal RAG follows *retrieve-then-read* process. Initial work focused on enhancing the retrieval phase, primarily by learning more effective multimodal embeddings. Pioneering approaches aligned queries and text documents using contrastive learning Luo et al. (2023), while others fused similarity scores from pretrained CLIP Wei et al. (2024). To improve retrieval, subsequent methods employed fine-grained late interaction between visual and textual tokens Lin et al. (2023; 2024) or leveraged MLLMs with instruction tuning to produce multimodal embeddings Jiang et al. (2025); Liu et al. (2024b); Zhang et al. (2024b). A separate line of research has explored generative retrieval, using document identifiers Long et al. (2024) or enhancing generative retrieval via reinforcement learning Long et al. (2025).

Another line of research improves the read phase, typically by reranking or refining the retrieved candidates. Hierarchical systems first perform a coarse, image-based search and then refine the results with text-based or multimodal rerankers Caffagni et al. (2024); Yan & Xie (2024); Yang et al. (2025).

Motivated by these limitations, the text domain has shifted to *iterative RAG*, a paradigm that leverages an LLM’s reasoning through multiple rounds of retrieval and reasoning. In this iterative cycle, the model leverages its reasoning to guide intermediate steps, which transform queries to collect more relevant knowledge and synthesize newly retrieved knowledge to progressively update the reasoning itself. Shao et al. (2023); Trivedi et al. (2022); Xiong et al. (2024); Liu et al. (2024a); Yue et al. (2025); Gao et al. (2025). While previous work has shown promise with this approach in the text-only domain, it has largely focused on refining a single subquery of decomposing multi-hop questions at each step. Extending this to the more complex multimodal domain remains an open challenge.

This challenge arises because a naive adaptation of the *iterative RAG* is insufficient for the multimodal domain, which introduces two distinct considerations: (i) it requires retrieving diverse knowledge by exploring multiple facets of a visually grounded entity and its related textual knowledge across modalities, and (ii) it demands compositional reasoning to synthesize the visual entity with its corresponding knowledge by integrating a diverse set of visual-to-visual, visual-to-text, and text-to-text factual links.

Others leverage the reasoning capabilities of MLLMs to self-reflect on retrieval needs and evaluate relevance Cocchi et al. (2025), generate semantic tags for consistency and reranking based on relevance scores Ling et al. (2025). While effective, these methods largely adhere to *retrieve-then-read* process. In contrast, MI-RAG introduces a dynamic loop that iterates between reasoning-guided query refinement and retrieval-augmented reasoning to progressively solve knowledge-intensive VQA tasks.

2.2 ITERATIVE RAG

When single-step retrieval is insufficient for complex, multi-hop questions, *iterative RAG* has emerged as a powerful paradigm in the text-only domain. These methods typically use an iterative loop to refine queries and retrieve new knowledge to improve subsequent iterations. Query transformation techniques are central to this process and include query expansion, which uses pseudo-answers to formulate richer queries Shao et al. (2023); Wang et al. (2024); query generation, which decomposes complex questions into simpler, answerable sub-queries Zhang et al. (2025); Liu et al. (2024a); and query planning, where a model strategically decides when and what to retrieve Trivedi et al. (2022); Yu et al. (2024).

To guide the subsequent query transformation, the LLM performs retrieval-augmented reasoning. This involves synthesizing newly retrieved information into a reasoning record. Common strategies include summarizing retrieved passages Jiang et al. (2024c); Zhang et al. (2025), extracting direct evidence snippets Yu et al. (2024), or generating pseudo-answers for intermediate sub-queries, often with chain-of-thought prompting Shao et al. (2023); Trivedi et al. (2022). However, these text-based iterative methods are primarily designed for multi-hop question decomposition, where the goal is to build a linear reasoning chain. Our work addresses knowledge-intensive VQA, which requires the composition of diverse knowledge across modalities.

3 METHOD

3.1 FRAMEWORK OF MULTIMODAL ITERATIVE RAG

Algorithm 1 MI-RAG

Require: $I, Q, \text{KB}_T, \text{KB}_M, \text{MLLM}, N$

Ensure: Final answer A

```

1:  $D \leftarrow \text{MLLM}(Q, I)$ 
2:  $Q_0^E \leftarrow \text{Expand}(Q, D)$ 
3:  $K_T \leftarrow \text{Ret}(\text{KB}_T, Q_0^E)$ 
4:  $K_M \leftarrow \text{Ret}(\text{KB}_M, I, Q_0^E)$ 
5:  $R_0 \leftarrow \text{Reasoning}(\text{MLLM}, Q, I, K_T, K_M, D)$ 
6: for  $i = 1$  to  $N$  do
7:    $Q_i^E \leftarrow \text{Expand}(Q, R_{i-1})$ 
8:    $Q_i^G \leftarrow \text{Generate}(\text{MLLM}, Q, R_0, \dots, R_{i-1})$ 
9:    $K_T \leftarrow \text{Ret}(\text{KB}_T, Q_i^E)$ 
10:   $K_T \leftarrow K_T \cup \text{Ret}(\text{KB}_T, Q_i^G)$ 
11:   $K_M \leftarrow \text{Ret}(\text{KB}_M, I, Q_i^E)$ 
12:   $K_M \leftarrow K_M \cup \text{Ret}(\text{KB}_M, I, Q_i^G)$ 
13:   $R_i \leftarrow \text{Reasoning}(\text{MLLM}, Q, I, K_{\text{text}}, K_{\text{mm}})$ 
14: end for
15:  $A \leftarrow \text{MLLM}(Q, I, \{R_0, R_1, \dots, R_N\})$ 
16: return  $A$ 

```

Finally, the model derives the final answer over the accumulated records (Line 15; Section 3.6).

As detailed in Algorithm 1, the MI-RAG framework processes multimodal queries (an image I and question Q), through iterative retrieval and reasoning. For conciseness in the pseudocode, we use the following abbreviations: KB_T for text KB, KB_M for multimodal KB, K_T for text passages, K_M for image-text pairs, Ret for Retrieve, D for image description, R for reasoning record and N for iteration counts. This iterative process begins with the generation of initial reasoning records (Lines 1–5; Section 3.2). Subsequently, in each iteration, MI-RAG leverages the accumulated reasoning record to formulate the multi-query (Lines 7–8; Section 3.3) and perform a joint search using the multi-query across heterogeneous KBs (Lines 9–12; Section 3.4), thereby dynamically gathering diverse and relevant knowledge. Following retrieval, MI-RAG updates the reasoning record by summarizing newly acquired knowledge about the queries (Line 13; Section 3.5).

3.2 INITIAL REASONING RECORD GENERATION

The initial reasoning record is generated by leveraging the retrieved knowledge with internal MLLM knowledge. Specifically, given a multimodal query, the MLLM generates an image description D

corresponding to the question. We perform query expansion, yielding expanded query $Q_0^E = [Q, D]$. This query Q_0^E is then used to retrieve knowledge from our heterogeneous KBs, collecting both text passages and image-text pairs. Finally, the model synthesizes retrieved diverse knowledge and descriptions into a reasoning record. This initial process generates the first reasoning record to bootstrap our iterative framework.

3.3 REASONING-GUIDED MULTI-QUERY TRANSFORMATION

MI-RAG employs a reasoning-guided multi-query transformation that leverages the MLLM’s intermediate reasoning steps to dynamically reformulate the query. This process uses the accumulated reasoning records to dynamically generate a set of complementary queries, ensuring a comprehensive search for multifaceted knowledge across modalities:

Query Expansion: This method leverages the latest reasoning record to expand the original query. The resulting query is designed to reflect the model’s latest reasoning, which enhances retrieval performance while preserving the original question’s intent.

Query Generation: This method produces a set of sub-queries designed to explore alternative reasoning paths, resolve ambiguities, or explicitly seek out missing facts identified during the analysis of the reasoning record.

We provide details of the prompt templates used to guide this transformation in Appendix Section A.

3.4 JOINT SEARCH ACROSS HETEROGENEOUS KBs

To enhance compositional reasoning, it is crucial to retrieve diverse knowledge across modalities. To acquire the a diverse set of factual knowledge, we perform a joint search over two heterogeneous KBs: a multimodal KB and a textual KB. The multimodal KB provides image-text pairs for visual grounding of entities, while the textual KB offers broad knowledge that extends beyond these pairs. Each query from the multi-query is used to retrieve candidates from both KBs simultaneously. To balance the token budget with broad knowledge coverage, our strategy retrieves twice as many text passages as image-text pairs, collecting up to 20 passages and 10 image-text pairs per iteration. The implementation details for multimodal retrieval are provided in Appendix C.

Retrieval from textual KB: The textual KB is queried using the multi-query. A text embedding model is used to retrieve the top-k passages based on semantic similarity.

Retrieval from multimodal KB: In contrast to prior methods that often rely on large, specialized retrievers, MI-RAG employs a lightweight retrieval strategy. We utilize a multimodal similarity scoring approach Changin et al. (2025) to support query transformation. For each candidate image-text pair, the similarity score is the average of two components: (1) a text-to-text similarity between the candidate’s text and the transformed query; and (2) a fixed image-to-image similarity between the candidate’s image and the input query image, which maintains constant visual relevance across iterations.

3.5 GENERATE REASONING RECORD WITH KNOWLEDGE

At each iteration, a reasoning record is generated by summarizing the newly retrieved knowledge. The MLLM synthesizes relevant evidence from visual entities and related text knowledge. This process utilizes the MLLM’s compositional reasoning to generate a reasoning record that captures relevant evidence. By iteratively enriching its understanding with these reasoning records, the model maintains a coherent reasoning path and enables more precise query transformations in subsequent steps. We provide details of the prompt in Appendix Section A.

3.6 FINAL ANSWER GENERATION

Upon completion of the N iterative cycles, MI-RAG generates the final answer. In this stage, MLLM synthesizes the original question Q , the input image I , and the accumulated reasoning records $\{R_0, \dots, R_N\}$ to produce an evidence-based answer.

4 EXPERIMENTS

4.1 EXPERIMENT SETUP

Datasets: Our evaluation is conducted on three diverse, knowledge-intensive VQA benchmarks: validation split of InfoSeek Chen et al. (2023), validation split of OK-VQA Marino et al. (2019), and test split of Encyclopedic VQA Mensink et al. (2023). For InfoSeek, we follow the setup of PreFLMR Lin et al. (2024) and utilize the validation split provided by the M2KR benchmark.

Knowledge bases: To provide the necessary external knowledge, our framework retrieves text passages and image-text pairs from heterogeneous KBs, which are held constant across all experiments: a Wikipedia text corpus provided by FlashRAG Jin et al. (2024) and a 2M image-text pair collection from Encyclopedic VQA.

Models: To assess how performance scales with reasoning ability, we primarily use two model variants: Gemma-3 Team et al. (2025) and Gemini-2.5-Flash Comanici et al. (2025). Our framework employs lightweight retrievers. For the multimodal retrieval of image-text pairs, we compute a multimodal similarity score using image embeddings from SigLIP2-SO-400m Tschannen et al. (2025) and text embeddings from ModernBERT Warner et al. (2024). For the retrieval of text passages, we use E5-base-v2 Wang et al. (2022), following the setup in FlashRAG Jin et al. (2024).

Evaluation metrics: We evaluate MI-RAG using standard metrics for each benchmark to evaluate accuracy and retrieval recall. For accuracy, we report the BERT matching score (BEM) Bulian et al. (2022) on Encyclopedic VQA. On the InfoSeek dataset, we measure Exact Match (EM) accuracy. To constrain the model’s answer to a single exact entity for this metric, we employ a 4-shot prompting strategy using examples from the training split. The full prompt template and further details are available in Appendix D. For OK-VQA, we use the standard VQA-score Marino et al. (2019) and a Cover Exact Match (Cover EM) Jiang et al. (2024a); Yue et al. (2025), which checks if the ground-truth answer is contained within the response. To assess retrieval performance, we use two metrics based on ground-truth annotation availability. Retrieval quality is measured using Recall of ground-truth entities where available, and Pseudo-Relevance Recall (PRR) otherwise Luo et al. (2021).

4.2 RETRIEVAL PERFORMANCE ON VQA BENCHMARKS

Table 1: Recall comparison on the InfoSeek and Encyclopedic VQA. FT column with ✓ indicates methods fine-tuned on the target dataset. Methods marked with † employ a reranking step after retrieval. Our vanilla method (§) uses a single query with expansion to retrieve K pairs from the multimodal KB, reporting average recall across iterations for fair comparison. Our full framework (*) reports the cumulative recall after 4 iterations. We report it on R@5, as each queries retrieve fewer than five pairs on average. The best and second-best overall accuracies are highlighted in **bold** and with an underline, respectively.

FT	Method	InfoSeek Validation			Encyclopedic VQA		
		R@5	R@10	R@20	R@5	R@10	R@20
×	CLIP ViT-L/14 Radford et al. (2021)	54.0	61.6	68.6	7.7	12.1	16.5
×	SigLIP2-So400m Tschannen et al. (2025)	52.5	60.2	68.3	30.8	36.6	41.9
×	EVA-CLIP-8B Sun et al. (2023)	67.1	73.0	77.9	31.3	41.0	48.8
✓	Wiki-LLaVA Caffagni et al. (2024)	-	66.1	71.9	-	9.9	13.2
✓	LLM-RA Jian et al. (2024)	53.8	-	-	-	-	-
✓	mR ² AG† Zhang et al. (2024a)	-	65.0	71.0	-	-	-
✓	ReflectiVA† Cocchi et al. (2025)	<u>77.6</u>	-	<u>86.4</u>	36.1	-	<u>49.8</u>
✓	EchoSight† Yan & Xie (2024)	<u>74.0</u>	<u>77.4</u>	<u>77.9</u>	<u>47.9</u>	<u>48.8</u>	<u>48.8</u>
✓	OMGM Yang et al. (2025)	73.9	80.0	84.8	41.2	49.8	58.7
✓	OMGM† Yang et al. (2025)	80.8	<u>83.6</u>	84.8	55.7	58.1	58.7
×	ReAuSE Long et al. (2025)	59.5	-	-	-	-	-
×	Ours (Gemma-3-4B)‡	80.8	85.6	89.7	39.1	44.3	<u>49.8</u>
×	Ours (Gemma-3-4B)*	88.0	-	-	53.6	-	-
×	Ours (Gemini-Flash-2.5)*	92.1	-	-	62.4	-	-

As shown in Table 1, our MI-RAG framework demonstrates highly effective retrieval without any task-specific fine-tuning. We analyze its performance by highlighting three key findings: the effectiveness of reasoning-guided queries in a lightweight setup, MI-RAG’s performance boost from the iterative process, and the framework’s inherent synergy with larger MLLMs.

To evaluate our reasoning-guided query transformation, we provide a vanilla method (\ddagger), which uses a single query with a multimodal KB, a small 4B MLLM, and a lightweight retriever for fair comparison, which contrasts with approaches that employ larger retrievers and use MLLM for reranking. Even under these constraints, our method is highly effective, achieving a top R@20 score of 89.7% on InfoSeek and the second-highest R@20 on Encyclopedic VQA.

Our full framework (*) performs multiple rounds of multi-query searches across heterogeneous KBs to progressively accumulate multifaceted knowledge across modalities. The results show significant gains in cumulative recall, reaching 88.0% (+7.2%) on InfoSeek and 53.6% (+14.5%) on Encyclopedic VQA.

Finally, we analyze MI-RAG’s scalability by evaluating its two core components: the MLLM and the retriever. As shown in Table 1, scaling the MLLM from Gemma-3-4B to Gemini-Flash-2.5 consistently improves performance. This result confirms that a more capable MLLM enhances both query transformation and compositional reasoning. In Section 6.1, we demonstrate that scaling the retriever provides a further performance boost.

Table 2: Recall comparison on the OK-VQA benchmark when utilizing Wikipedia as the knowledge source. Symbols denote: fine-tuning (\checkmark); reranking (\dagger); our vanilla baseline (\ddagger); and our MI-RAG framework (*). The best and second-best overall accuracies are highlighted in **bold** and with an underline, respectively.

FT	Methods	OK-VQA		
		PRR@5	PRR@10	PRR@20
\checkmark	ReViz-ICT	61.9	72.6	<u>81.1</u>
\checkmark	GeMKR	70.8	79.1	-
\checkmark	FLMR	68.1	78.0	-
\checkmark	Pre-FLMR	68.6	-	-
\checkmark	ReAuSE	88.0	91.3	-
\times	OMGM \dagger	73.4	-	-
\times	Ours (Gemma-3-4B) \ddagger	<u>77.1</u>	<u>85.4</u>	91.2
\times	Ours (Gemma-3-4B)*	95.2	-	-
\times	Ours (Gemini-Flash-2.5)*	97.1	-	-

On the OK-VQA benchmark, MI-RAG demonstrates strong retrieval performance, as detailed in Table 2. Our vanilla method (\ddagger), despite its lightweight setup, shows competitive performance. Enabling the full MI-RAG provides a substantial boost to 95.2% (18.1%) for the same 4B model. A more powerful MLLM with stronger reasoning achieves 97.1% recall, outperforming all prior work.

This robust performance contrasts sharply with prior methods, which often exhibit a performance trade-off across different benchmarks. For instance, ReAuSE excels in its trained knowledge domain (OK-VQA) but fails to generalize to InfoSeek, whereas OMGM shows the reverse pattern. In contrast, our method shows high performance across all benchmarks.

4.3 ACCURACY ON VQA BENCHMARKS

As demonstrated in Table 3, our MI-RAG framework establishes a new state-of-the-art on the Encyclopedic VQA benchmark. To isolate the contribution of our iterative reasoning, we first evaluate a setting with a strong initial retrieval provided by Google Lens. This configuration reveals that performance scales directly with the MLLM’s reasoning capacity: accuracy improves from a competitive 62.8% with Gemma-3-4B to a state-of-the-art 75.5% with Gemini-2.5-Flash. This highlights the synergy between a high-quality initial retrieval and the model’s ability to iteratively refine it, a analysis further explored in Section 6.1.

In the more challenging setting without Google Lens, we use reasoning records generated by Gemini-2.5-Flash with our lightweight retriever setup. When these records are applied to LLaVA-MORE-8B checkpoint from ReflectiVA as the answerer, our framework achieves a competitive accuracy of 50.4%. When Gemini-2.5-Flash is used as the answerer, our method establishes 61.4% accuracy.

On the InfoSeek benchmark, MI-RAG translates its strong retrieval performance into state-of-the-art accuracy, as detailed in Table 4. Our method achieves 48.0% accuracy with Gemini-2.5-Flash and improves to 51.7% with GPT-4o as the answerer, outperforming all prior work. This is driven by our iterative process, where accumulated reasoning records enable robust compositional reasoning over

Table 3: Accuracy comparison on the Encyclopedic VQA benchmark. A checkmark (✓) indicates fine-tuning, a dagger (†) denotes MLLM-based reranking, and an asterisk (*) marks the use of ReflectiVA checkpoints. Our framework’s Gemma-series models generate their own reasoning records, whereas other models use records provided by Gemini-2.5-Flash.

Google Lens	FT	Method	Model	Single-hop	All
	✓	Wiki-LLaVA Caffagni et al. (2024)	LLaVA-v1.5-7B	21.8	–
	✓	EchoSight† Yan & Xie (2024)	Mistral-7B	35.5	–
	✓	ReflectiVA† Cocchi et al. (2025)	LLaVA-MORE-8B	35.5	–
×	✓	MMKB-RAG† Ling et al. (2025)	Qwen2-VL-7B	39.7	35.9
	✓	OMGM† Yang et al. (2025)	LLaVA-v1.5-7B	50.2	–
	✓	OMGM† Yang et al. (2025)	GPT-4o	51.2	–
	✓	Ours	LLaVA-MORE-8B*	50.4	49.2
	×	Ours	Gemini-2.5-Flash	61.4	62.9
	×	HAMMR Castrejon et al. (2024)	PaLI-X	47.8	–
	×	LVLm cascade Alazraki et al. (2023)	PaLM, GPT-3, PaLI	53.4	–
✓	✓	mR ² AG† Zhang et al. (2024a)	LLaVA-v1.5-7B	55.9	51.8
	×	Ours	Gemma-3-4B	62.8	63.7
	×	Ours	Gemini-2.5-Flash	75.5	70.8

Table 4: Accuracy comparison on the InfoSeek benchmark: the top section evaluates the full validation set, while the bottom section assesses a 5K validation split. A checkmark (✓) in the FT column indicates fine-tuning, a dagger (†) denotes a reranking step, and an asterisk (*) marks the use of checkpoints from ReflectiVA. Our framework’s Gemma-series models generate their own reasoning records, whereas other models use records provided by Gemini-2.5-Flash.

FT	Method	Retriever	Model	Acc
✓	Wiki-LLaVA Caffagni et al. (2024)	CLIP-ViT-L	LLaVA-1.5-7B	28.9
✓	EchoSight† Yan & Xie (2024)	EVA-CLIP-8B	LLaMA3-8B	31.3
✓	mR ² AG† Zhang et al. (2024a)	CLIP-ViT-L	LLaVA-1.5-7B	40.2
✓	ReflectiVA† Cocchi et al. (2025)	EVA-CLIP-8B	LLaVA-MORE-8B	40.1
✓	MMKB-RAG† Ling et al. (2025)	PreFLMR ViT-G	Qwen2-VL-7B	36.7
✓	OMGM† Yang et al. (2025)	EVA-CLIP-8B	LLaVA-1.5-7B	43.5
✓	OMGM† Yang et al. (2025)	EVA-CLIP-8B	GPT-4o	42.1
✓	RA-VQA-v2 Lin et al. (2024)	PreFLMR ViT-G	BLIP2-Flan-T5-XL	30.7
✓	MMKB-RAG Ling et al. (2025)	PreFLMR ViT-G	Qwen2-VL-7B	34.7
✓	MUKA Deng et al. (2025)	MUKA	VILA-13B	42.5
✓			LLaVA-MORE-8B*	45.1
×			Gemma-3-4B	33.1
×	Ours	SigLIP2-SO-400m	Gemini-2.5-Flash	48.0
×			GPT-4o	51.7

multifaceted, diverse knowledge. The strength of this iterative reasoning is further demonstrated by its ability to improve ReflectiVA’s LLaVA-MORE-8B checkpoint to 45.1%.

Table 5: Comparison of accuracy based on two metrics: Cover EM, which checks if the ground-truth answer is included in the response, and Exact Match, which requires the response to match the ground-truth answer exactly.

Model	InfoSeek Validation		InfoSeek Human		OK-VQA	
	EM	CEM	EM	CEM	EM	CEM
Gemma-3-4B	33.1	50.4	32.3	39.3	43.3	68.8
Gemini-2.5-Flash	50.8	61.3	40.5	44.9	57.3	71.0

Recent MLLMs generate detailed, free-form responses by leveraging multi-stage post-training to better align with human preferences, making strict exact match (EM) an inadequate metric for a comprehensive evaluation, as noted in prior work Shao et al. (2023); Cocchi et al. (2025). Consequently, metrics like Cover EM (CEM), which verify the inclusion of the ground-truth answer within a longer response, are increasingly used Jiang et al. (2024a); Yue et al. (2025); Wang et al. (2025).

5 ABLATIONS

We conduct ablation studies to evaluate MI-RAG’s core components. For efficiency, all experiments are performed on downsampled InfoSeek and Encyclopedic VQA subsets using Gemini-2.5-Flash as the MLLM. We report performance using cumulative recall, along with CoverEM on InfoSeek and BEM on Encyclopedic VQA. We strictly controlled the retrieval budget to ensure a fair comparison. For our default heterogeneous KB setting, we retrieve 20 text passages and 10 image-text pairs. To maintain a comparable budget in multimodal KB, we retrieve 20 pairs. This total retrieval budget is held constant across both single-query and multi-query. We provide details of the downsampling algorithm in Appendix Section B.

5.1 ABLATION OF COMPONENTS

Table 6: Ablation of MIRAG on the InfoSeek validation subset and Encyclopedic VQA test subset.

Components			InfoSeek		Encyclopedic VQA	
Multi Query	Hetero. KB	Iter.	Acc	Recall	Acc	Recall
×	×	×	46.70	87.28	50.78	47.06
✓	×	×	49.44	90.34	52.94	49.02
×	✓	×	49.21	88.08	51.18	52.75
✓	✓	×	54.11	91.43	56.67	57.25
✓	✓	✓	61.84	94.36	63.33	67.25

Our ablation analysis in Table 6 reveals the impact of each component. We establish a strong baseline using a vanilla RAG system over a multimodal KB, enhanced with our initial query expansion, which integrates the MLLM’s knowledge. Introducing the reasoning-guided multi-query yields a substantial accuracy gain by gathering the multifaceted knowledge. Moreover, employing our heterogeneous KB is crucial for compositional reasoning, as it enables the model to compose visually-grounded knowledge with the broad textual knowledge. Combining these two components creates a crucial synergy for compositional reasoning. However, the iterative process delivers the most significant improvement across all datasets.

5.2 IMPACT OF ITERATIVE REFINEMENT

Table 7: Performance over iterations on the InfoSeek and Encyclopedic VQA.

Iter.	InfoSeek		Encyclopedic VQA	
	Acc	Recall	Acc	Recall
1	55.72	92.13	58.46	65.10
2	59.10	92.95	60.86	66.27
3	61.41	93.44	61.96	66.86
4	61.84	94.36	63.33	67.25

Our ablation analysis in Table 6 reveals the impact of each component. We establish a strong baseline using a vanilla RAG system over a multimodal KB, enhanced with our initial query expansion, which integrates the MLLM’s knowledge. Introducing the reasoning-guided multi-query yields a substantial accuracy gain by gathering the multifaceted knowledge. Moreover, employing our heterogeneous KB is crucial for compositional reasoning, as it enables the model to compose visually-grounded

knowledge with the broad textual knowledge. Combining these two components creates a crucial synergy for compositional reasoning. However, the iterative process delivers the most significant improvement across all datasets.

To further investigate the benefits of iterative refinement, we analyze performance across multiple iterations, with results presented in Table 7. The study confirms that iterative processing is a primary driver of accuracy, and performance is consistently improving over the vanilla baseline across all datasets. The most substantial gains are typically realized within the first two iterations, validating the efficacy of the core refinement loop. As visualized in Figure 2, these gains begin to saturate in later iterations.

5.3 IMPACT OF HETEROGENEOUS KB

Table 8: Ablation on the KB configuration, showing the performance after 4 iterations. Heterogeneous KB refers to the use of both KB, while Multimodal restricts retrieval to only the multimodal KB.

KB Config.	InfoSeek		Encyclopedic VQA	
	Acc	Recall	Acc	Recall
Multimodal	57.49	91.79	56.86	58.63
Heterogeneous	61.84	94.36	63.33	67.25

As shown in Table 8, we evaluate the impact of heterogeneous KB. Applying our reasoning-guided multi-query approach to the multimodal KB alone yields a high recall, demonstrating its ability to retrieve visually grounded information. However, its precision remains limited, indicating that visually grounded information is often insufficient for compositional reasoning. By combining heterogeneous sources, the MI-RAG enables the model to perform compositional reasoning, leveraging the diverse, relevant evidence to refine its search and generate more accurate reasoning records for the final answer.

6 ANALYSIS

6.1 SCALING RETRIEVERS

Building upon the established benefits of scaling MLLM, we now investigate the impact of scaling the retriever. We investigated this employing a larger vision encoder (SigLIP2-G) and a text embedding model (Qwen3-Embedding-0.6B). On the InfoSeek validation split, when using Gemini-2.5-Flash for MI-RAG, this enhanced retrieval improves accuracy to 66.7% (+6.4%) and cumulative recall to 95.2% (+3.1%). Similarly, on the Encyclopedic VQA test split, the scaled retriever paired with the Gemma-3-4B enhances accuracy to 50.2% (+1.9%) and cumulative recall 65.7% (+12.1%). These findings confirm that improving retrieval capability provides significant benefits for MI-RAG’s performance, validating the synergistic design.

6.2 ANALYSIS OF ITERATIVE PERFORMANCE




Figure 2: Accuracy and recall of MI-RAG on InfoSeek subset across 9 iterations.

We analyze how iterative refinement impacts MI-RAG’s performance by measuring accuracy and recall across iterations. As shown in Figure 2, performance improves consistently with each step. The initial iterations deliver significant gains. Although the rate of improvement moderates in later steps, the model continues to achieve substantial gains in accuracy and recall. This performance improvement comes with an associated computational cost for each iteration, which we detail in Appendix E.

6.3 TOP-K SENSITIVITY ANALYSIS

Table 9: Top-k sensitivity analysis on the InfoSeek validation subset. k indicates the number of retrieved image-text pairs.

Model	Metric	$k = 10$	$k = 20$
Gemma-3-4B	Acc	52.66	48.95
	Recall	90.82	94.52
Gemini-2.5-Flash	Acc	61.84	65.70
	Recall	94.36	95.97

Our sensitivity analysis on the InfoSeek validation subset (Table 9) reveals that the benefit of a larger retrieval budget is only beneficial if the MLLM is capable enough to handle the additional context. As shown in Table 9, the results reveal that simply increasing the retrieval budget is not always beneficial. For instance, Gemma-4 shows a degradation in accuracy when k is increased from 10 to 20, suggesting that the additional context may potentially distract, hindering its ability to gather the correct evidence.

7 CONCLUSION

In this work, we introduced MI-RAG, a novel multimodal iterative RAG framework that addresses key challenges in knowledge-intensive VQA. MI-RAG employs a reasoning-guided multi-query transformation that dynamically explores multiple facets of an entity and its related textual knowledge across modalities. To facilitate compositional reasoning, its iterative process uses this retrieved evidence to progressively synthesize visual entities and corresponding textual knowledge, effectively integrating a diverse set of factual links. Our results demonstrate that MI-RAG is an effective and scalable paradigm for advancing compositional reasoning in knowledge-intensive VQA. Furthermore, our analysis indicates clear pathways for future work, such as scaling components by integrating web-scale search or dynamically adjusting the retrieval budget based on model capability.

REFERENCES

- Lisa Alazraki, Lluís Castrejon, Mostafa Dehghani, Fantine Huot, Jasper Uijlings, and Thomas Mensink. How (not) to ensemble llms for vqa. In *Proceedings on*, pp. 1–20. PMLR, 2023.
- Chen Amiraz, Florin Cuconasu, Simone Filice, and Zohar Karnin. The distracting effect: Understanding irrelevant passages in rag. *arXiv preprint arXiv:2505.06914*, 2025.
- Jannis Bulian, Christian Buck, Wojciech Gajewski, Benjamin Börschinger, and Tal Schuster. Tomayto, tomahto. beyond token-level answer equivalence for question answering evaluation. In Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang (eds.), *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 291–305, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.20. URL <https://aclanthology.org/2022.emnlp-main.20/>.
- Davide Caffagni, Federico Cocchi, Nicholas Moratelli, Sara Sarto, Marcella Cornia, Lorenzo Baraldi, and Rita Cucchiara. Wiki-llava: Hierarchical retrieval-augmented generation for multimodal llms. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1818–1826, 2024.
- Lluís Castrejon, Thomas Mensink, Howard Zhou, Vittorio Ferrari, Andre Araujo, and Jasper Uijlings. Hammr: Hierarchical multimodal react agents for generic vqa. *arXiv preprint arXiv:2404.05465*, 2024.
- Choi Changin, Lim Sungjun, and Rhee Wonjong. Enhancing retrieval-augmented audio captioning with generation-assisted multimodal querying and progressive learning, 2025. URL <https://arxiv.org/abs/2410.10913>.
- Yang Chen, Hexiang Hu, Yi Luan, Haitian Sun, Soravit Changpinyo, Alan Ritter, and Ming-Wei Chang. Can pre-trained vision and language models answer visual information-seeking questions? In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 14948–14968, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.925. URL <https://aclanthology.org/2023.emnlp-main.925/>.
- Zhanpeng Chen, Chengjin Xu, Yiyang Qi, and Jian Guo. Mllm is a strong reranker: Advancing multimodal retrieval-augmented generation via knowledge-enhanced reranking and noise-injected training. *arXiv preprint arXiv:2407.21439*, 2024.
- Federico Cocchi, Nicholas Moratelli, Marcella Cornia, Lorenzo Baraldi, and Rita Cucchiara. Augmenting Multimodal LLMs with Self-Reflective Tokens for Knowledge-based Visual Question Answering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025.
- Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, et al. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*, 2025.
- Florin Cuconasu, Giovanni Trappolini, F. Siciliano, Simone Filice, Cesare Campagnano, Yoelle Maarek, Nicola Tonello, and Fabrizio Silvestri. The power of noise: Redefining retrieval for rag systems. In *Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2024. URL <https://api.semanticscholar.org/CorpusID:267301416>.
- Lianghao Deng, Yuchong Sun, Shizhe Chen, Ning Yang, Yunfeng Wang, and Ruihua Song. Muka: Multimodal knowledge augmented visual information-seeking. In *Proceedings of the 31st International Conference on Computational Linguistics*, pp. 9675–9686, 2025.
- Yunfan Gao, Yun Xiong, Yijie Zhong, Yuxi Bi, Ming Xue, and Haofen Wang. Synergizing rag and reasoning: A systematic review. *arXiv preprint arXiv:2504.15909*, 2025.

- Wenyu Huang, Pavlos Vougiouklis, Mirella Lapata, and Jeff Z Pan. Masking in multi-hop qa: An analysis of how language models perform with context permutation. *arXiv preprint arXiv:2505.11754*, 2025.
- Pu Jian, Donglei Yu, and Jiajun Zhang. Large language models know what is key visual entity: An llm-assisted multimodal retrieval for vqa. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 10939–10956, 2024.
- Jinhao Jiang, Jiayi Chen, Junyi Li, Ruiyang Ren, Shijie Wang, Wayne Xin Zhao, Yang Song, and Tao Zhang. Rag-star: Enhancing deliberative reasoning with retrieval augmented verification and refinement. *arXiv preprint arXiv:2412.12881*, 2024a.
- Ting Jiang, Minghui Song, Zihan Zhang, Haizhen Huang, Weiwei Deng, Feng Sun, Qi Zhang, Deqing Wang, and Fuzhen Zhuang. E5-v: Universal embeddings with multimodal large language models. *arXiv preprint arXiv:2407.12580*, 2024b.
- Zhouyu Jiang, Mengshu Sun, Lei Liang, and Zhiqiang Zhang. Retrieve, summarize, plan: Advancing multi-hop question answering with an iterative approach. *arXiv preprint arXiv:2407.13101*, 2024c.
- Ziyan Jiang, Rui Meng, Xinyi Yang, Semih Yavuz, Yingbo Zhou, and Wenhui Chen. VLM2vec: Training vision-language models for massive multimodal embedding tasks. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=TE0KOzWYAF>.
- Jiajie Jin, Yutao Zhu, Guanting Dong, Yuyao Zhang, Xinyu Yang, Chenghao Zhang, Tong Zhao, Zhao Yang, Zhicheng Dou, and Ji-Rong Wen. Flashrag: A modular toolkit for efficient retrieval-augmented generation research. *arXiv preprint arXiv:2405.13576*, 2024.
- Sheng-Chieh Lin, Chankyu Lee, Mohammad Shoeybi, Jimmy Lin, Bryan Catanzaro, and Wei Ping. MM-EMBED: UNIVERSAL MULTIMODAL RETRIEVAL WITH MULTIMODAL LLMS. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=i45NQb2iKO>.
- Weizhe Lin, Jinghong Chen, Jingbiao Mei, Alexandru Coca, and Bill Byrne. Fine-grained late-interaction multi-modal retrieval for retrieval augmented visual question answering. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL <https://openreview.net/forum?id=IWWWu1AX7g>.
- Weizhe Lin, Jingbiao Mei, Jinghong Chen, and Bill Byrne. PreFLMR: Scaling up fine-grained late-interaction multi-modal retrievers. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 5294–5316, Bangkok, Thailand, August 2024. Association for Computational Linguistics. URL <https://aclanthology.org/2024.acl-long.289>.
- Zihan Ling, Zhiyao Guo, Yixuan Huang, Yi An, Shuai Xiao, Jinsong Lan, Xiaoyong Zhu, and Bo Zheng. Mmkb-rag: A multi-modal knowledge-based retrieval-augmented generation framework. *arXiv preprint arXiv:2504.10074*, 2025.
- Yanming Liu, Xinyue Peng, Xuhong Zhang, Weihao Liu, Jianwei Yin, Jiannan Cao, and Tianyu Du. RA-ISF: Learning to answer and understand from retrieval augmentation via iterative self-feedback. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 4730–4749, Bangkok, Thailand, August 2024a. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-acl.281. URL <https://aclanthology.org/2024.findings-acl.281/>.
- Yikun Liu, Pingan Chen, Jiayin Cai, Xiaolong Jiang, Yao Hu, Jiangchao Yao, Yanfeng Wang, and Weidi Xie. Lamra: Large multimodal model as your advanced retrieval assistant. *arXiv preprint arXiv:2412.01720*, 2024b.
- Xinwei Long, Jiali Zeng, Fandong Meng, Zhiyuan Ma, Kaiyan Zhang, Bowen Zhou, and Jie Zhou. Generative multi-modal knowledge retrieval with large language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 18733–18741, 2024.

- Xinwei Long, Zhiyuan Ma, Ermo Hua, Kaiyan Zhang, Biqing Qi, and Bowen Zhou. Retrieval-augmented visual question answering via built-in autoregressive search engines. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 24723–24731, 2025.
- Man Luo, Yankai Zeng, Pratyay Banerjee, and Chitta Baral. Weakly-supervised visual-retriever-reader for knowledge-based question answering. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih (eds.), *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 6417–6431, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.517. URL <https://aclanthology.org/2021.emnlp-main.517/>.
- Man Luo, Zhiyuan Fang, Tejas Gokhale, Yezhou Yang, and Chitta Baral. End-to-end knowledge retrieval with multi-modal queries. *arXiv preprint arXiv:2306.00424*, 2023.
- Kenneth Marino, Mohammad Rastegari, Ali Farhadi, and Roozbeh Mottaghi. Ok-vqa: A visual question answering benchmark requiring external knowledge. In *Proceedings of the IEEE/cvf conference on computer vision and pattern recognition*, pp. 3195–3204, 2019.
- Thomas Mensink, Jasper Uijlings, Lluís Castrejon, Arushi Goel, Felipe Cadar, Howard Zhou, Fei Sha, André Araujo, and Vittorio Ferrari. Encyclopedic vqa: Visual questions about detailed properties of fine-grained categories. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3113–3124, 2023.
- OpenRouter. Openrouter api, 2025. URL <https://openrouter.ai/docs/api-reference>. Accessed: 2025-05-21.
- Fabio Petroni, Patrick Lewis, Aleksandra Piktus, Tim Rocktäschel, Yuxiang Wu, Alexander H. Miller, and Sebastian Riedel. How context affects language models’ factual predictions. In *Automated Knowledge Base Construction*, 2020. URL <https://openreview.net/forum?id=025X0zPfn>.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PmlR, 2021.
- Zhihong Shao, Yeyun Gong, Yelong Shen, Minlie Huang, Nan Duan, and Weizhu Chen. Enhancing retrieval-augmented large language models with iterative retrieval-generation synergy. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 9248–9274, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.620. URL <https://aclanthology.org/2023.findings-emnlp.620/>.
- Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed H Chi, Nathanael Schärli, and Denny Zhou. Large language models can be easily distracted by irrelevant context. In *International Conference on Machine Learning*, pp. 31210–31227. PMLR, 2023.
- Quan Sun, Yuxin Fang, Ledell Wu, Xinlong Wang, and Yue Cao. Eva-clip: Improved training techniques for clip at scale. *arXiv preprint arXiv:2303.15389*, 2023.
- Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, et al. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*, 2025.
- Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. Interleaving retrieval with chain-of-thought reasoning for knowledge-intensive multi-step questions. *arXiv preprint arXiv:2212.10509*, 2022.
- Michael Tschannen, Alexey Gritsenko, Xiao Wang, Muhammad Ferjad Naeem, Ibrahim Alabdulmohsin, Nikhil Parthasarathy, Talfan Evans, Lucas Beyler, Ye Xia, Basil Mustafa, et al. Siglip 2: Multilingual vision-language encoders with improved semantic understanding, localization, and dense features. *arXiv preprint arXiv:2502.14786*, 2025.

- Fei Wang, Xingchen Wan, Ruoxi Sun, Jiefeng Chen, and Sercan Ö. Arik. Astute rag: Overcoming imperfect retrieval augmentation and knowledge conflicts for large language models, 2025. URL <https://arxiv.org/abs/2410.07176>.
- Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*, 2022.
- Zihao Wang, Anji Liu, Haowei Lin, Jiaqi Li, Xiaojian Ma, and Yitao Liang. Rat: Retrieval augmented thoughts elicit context-aware reasoning in long-horizon generation. *arXiv preprint arXiv:2403.05313*, 2024.
- Benjamin Warner, Antoine Chaffin, Benjamin Clavié, Orion Weller, Oskar Hallström, Said Taghadouini, Alexis Gallagher, Raja Biswas, Faisal Ladhak, Tom Aarsen, et al. Smarter, better, faster, longer: A modern bidirectional encoder for fast, memory efficient, and long context finetuning and inference. *arXiv preprint arXiv:2412.13663*, 2024.
- Cong Wei, Yang Chen, Haonan Chen, Hexiang Hu, Ge Zhang, Jie Fu, Alan Ritter, and Wenhua Chen. Uniir: Training and benchmarking universal multimodal information retrievers. In *European Conference on Computer Vision*, pp. 387–404. Springer, 2024.
- Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. Longmemeval: Benchmarking chat assistants on long-term interactive memory. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=pZiyCaVuti>.
- Siye Wu, Jian Xie, Jiangjie Chen, Tinghui Zhu, Kai Zhang, and Yanghua Xiao. How easily do irrelevant inputs skew the responses of large language models? *ArXiv*, abs/2404.03302, 2024. URL <https://api.semanticscholar.org/CorpusID:268889623>.
- Guangzhi Xiong, Qiao Jin, Xiao Wang, Minjia Zhang, Zhiyong Lu, and Aidong Zhang. Improving retrieval-augmented generation in medicine with iterative follow-up questions. In *Biocomputing 2025: Proceedings of the Pacific Symposium*, pp. 199–214. World Scientific, 2024.
- Yibin Yan and Weidi Xie. EchoSight: Advancing visual-language models with Wiki knowledge. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 1538–1551, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-emnlp.83. URL <https://aclanthology.org/2024.findings-emnlp.83/>.
- Wei Yang, Jingjing Fu, Rui Wang, Jinyu Wang, Lei Song, and Jiang Bian. Omgm: Orchestrate multiple granularities and modalities for efficient multimodal retrieval. *arXiv preprint arXiv:2505.07879*, 2025.
- Michihiro Yasunaga, Armen Aghajanyan, Weijia Shi, Rich James, Jure Leskovec, Percy Liang, Mike Lewis, Luke Zettlemoyer, and Wen-tau Yih. Retrieval-augmented multimodal language modeling. In *Proceedings of the 40th International Conference on Machine Learning, ICML’23*. JMLR.org, 2023.
- Tian Yu, Shaolei Zhang, and Yang Feng. Auto-rag: Autonomous retrieval-augmented generation for large language models. *arXiv preprint arXiv:2411.19443*, 2024.
- Zhenrui Yue, Honglei Zhuang, Aijun Bai, Kai Hui, Rolf Jagerman, Hansi Zeng, Zhen Qin, Dong Wang, Xuanhui Wang, and Michael Bendersky. Inference scaling for long-context retrieval augmented generation. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=FSjIrOmlvz>.
- Tao Zhang, Ziqi Zhang, Zongyang Ma, Yuxin Chen, Zhongang Qi, Chunfeng Yuan, Bing Li, Junfu Pu, Yuxuan Zhao, Zehua Xie, Jin Ma, Ying Shan, and Weiming Hu. mr²ag: Multimodal retrieval-reflection-augmented generation for knowledge-based vqa. *arXiv preprint arXiv:2411.15041*, 2024a. URL <https://arxiv.org/abs/2411.15041>.

Xin Zhang, Yanzhao Zhang, Wen Xie, Mingxin Li, Ziqi Dai, Dingkun Long, Pengjun Xie, Meishan Zhang, Wenjie Li, and Min Zhang. Gme: Improving universal multimodal retrieval by multimodal llms. *arXiv preprint arXiv:2412.16855*, 2024b.

Yue Zhang, Yafu Li, Leyang Cui, Deng Cai, Lemao Liu, Tingchen Fu, Xinting Huang, Enbo Zhao, Yu Zhang, Yulong Chen, et al. Siren’s song in the ai ocean: a survey on hallucination in large language models. *arXiv preprint arXiv:2309.01219*, 2023.

Zhuocheng Zhang, Yang Feng, and Min Zhang. Levelrag: Enhancing retrieval-augmented generation with multi-hop logic planning over rewriting augmented searchers. *arXiv preprint arXiv:2502.18139*, 2025.

A PROMPTS TEMPLATE FOR MI-RAG

Our Multimodal Iterative RAG (MI-RAG) framework employs structured prompts to dynamically refine its understanding and gather relevant knowledge. To generate initial reasoning records, we use a query-focused description of the input image to retrieve an initial set of knowledge. The core iterative loop then utilizes two prompts. First, the query generation in multi-query instructs the model to analyze the accumulated reasoning records and generate two questions. This step is crucial for progressively searching for more specific and helpful information. For the query expansion in multi-query, we simply concatenate the previous reasoning record. Second, the Reasoning Record generation prompt directs the model to synthesize the image and the newly retrieved knowledge into a query-focused summarization. This reasoning record is the result of compositional reasoning and improves subsequent retrieval iterations, and is used to derive the final answer.

```

1 # 1. Initial description generation
2 prompt = f"Question: {question}\n Concisely describe image which is
  ↳ relevant to question.\n"
3
4 -----
5 # 2. Query Expansion
6 prompt = f"Question: {question}\n{reasoning_record}\n"
7
8 -----
9 # 3. Query Generation Prompt
10 Question: {question}
11 Knowledge: {total_prediction}
12
13 Please first analyze all the information in a section named Analysis
14 ↳ (## Analysis).
15 Generate two follow-up questions to search for additional information
16 ↳ and helpful to confirm knowledge, in a section named Queries (##
17 ↳ Queries).
18 Your output should be in the following format:
19
20 ## Analysis
21 Analysis question and knowledge to ask context-specific queries that
22 ↳ helps to address question.
23 ## Queries
24 Question 1: question 1.
25 Question 2: question 2.
26
27 -----
28 # 3. Reasoning Record Generation Prompt
29 # This prompt instructs the model to synthesize information into a
30 ↳ coherent summary.
31
32 Question: {question}
33 Knowledge: {knowledge}
34
35 Based on image, description and knowledge, summarize correct and
36 ↳ relevant information with image and question.

```

Figure 1: Pseudo-code for prompt templates used in our MI-RAG framework. The Query Generation prompt drives the iterative retrieval process, while the Reasoning Record Generation prompt synthesizes information at each step.

B SUBSET DOWNSAMPLING PROCEDURES

To support an efficient analysis and design of our model, MI-RAG, we perform ablation studies on a compact and diverse subset of each dataset. We generate this subset using the iterative downsampling procedure detailed in Figure 2, which aims to eliminate redundancy.

```

1 # D: Input Dataset of questions
2 # Q: A single question from the dataset
3 # Emb_Q: The text embedding of a question Q
4 # t: The similarity threshold
5 # subset: Downsampled dataset
6
7 function DownSampleDataset(D, t):
8     subset = []
9     subset_emb = []
10
11     for Q in D:
12         is_redundant = False
13         Emb_Q = Encode(Q)
14
15         for emb in subset_emb:
16             if Similarity(Emb_Q, emb) > t:
17                 is_redundant = True
18                 break
19
20         if not is_redundant:
21             subset.append(Q)
22             subset_emb.append(Emb_Q)
23
24     return subset

```

Figure 2: Pseudo-code for downsampling: discard questions whose similarity to any in the subset exceeds threshold, yielding a non-redundant subset.

The algorithm greedily constructs a subset by adding a new question Q from the original dataset D only if it is sufficiently dissimilar to all questions already selected. Specifically, a question is considered redundant and discarded if the similarity of its embedding, Emb_Q , exceeds a predefined threshold with any embedding already in the subset. This threshold is adjusted for each dataset to yield a final subset containing approximately 500 diverse question-answer pairs.

C MULTIMODAL RETRIEVAL IMPLEMENTATIONS

To build our knowledge base, we processed the Wikipedia dataset from Enclopedia VQA, which contains 2 millions of image-caption pairs. The construction process involves generating a multimodal embedding for each pair and indexing them for efficient retrieval. For each sample, we extracted a normalized image embedding using a pretrained SigLIP model and a normalized text embedding using pretrained modernbert model which is trained with GTE method. These two vectors were then concatenated to form a multimodal embedding. Finally, all embedding is indexed using FAISS with an IndexFlatIP (Inner Product) to create a knowledge base. A corresponding metadata file was also created to map the index entries back to their original image paths and Wikipedia text sections. When encoding text embedding, we use a summary of each Wikipedia section. For the large retriever configuration of SigLIP2-g and Qwen3-Embedding-0.6B, we employ the image-to-mixture similarity proposed in RA-CM3 Yasunaga et al. (2023) and encode mixed embedding instead of image embedding.

At query time, we encode the input image and refined text query into the same multimodal embedding space as our knowledge base. We first generate normalized embeddings for the image and the text query separately. These vectors are then concatenated to form a single multimodal query vector. Finally, we perform a maximum inner product search against the knowledge base to retrieve the top-k entries with the highest multimodal similarity.

As shown in Table 1, we evaluated the retriever performance on the InfoSeek validation and Encyclopedia test splits. The results confirm two key points. First, using a multimodal query (image+text) that considers both visual and textual similarity consistently yields higher recall than using a unimodal (image) query alone. Second, we observed that our scaled retriever configuration (SigLIP2-g

Table 1: Performance analysis of multimodal similarity on the InfoSeek validation split and Encyclopedia test split.

Retriever	Dataset	Query Modality	R@1	R@5	R@10
SigLIP2-SO400m+ ModernBert-GTE	InfoSeek	image	52.5	60.2	68.3
		image+text	57.8	65.3	72.3
	Encyclopedia	image	30.8	36.6	41.8
		image+text	34.9	40.5	45.3
SigLIP2-g+ Qwen3-Embedding-0.6B	InfoSeek	image	66.7	72.7	77.5
		image+text	69.4	76.2	81.1
	Encyclopedia	image	36.2	41.9	46.4
		image+text	43.1	48.7	54.5

+ Qwen3-Embedding-0.6B) performs better than the more lightweight setup (SigLIP2-SO400m + ModernBert-GTE). Despite the performance gap, we used the lightweight setup for our main experiments. This choice ensures a fair comparison and emphasizes that our framework’s primary improvements stem from its iterative reasoning process, not from relying on a stronger base retriever.

D FEW-SHOT PROMPTING FOR ANSWER EXTRACTION

To evaluate performance on the Exact Match metric for the InfoSeek dataset, we employed a few-shot prompting strategy to guide the model toward generating single exact answer. For each question in the validation set, we provided the model with three demonstrations drawn from the training split using question similarity. These demonstrations consist of an image, a context of reasoning records, a question, and the ground-truth answer. By presenting these structured examples, we condition the model to generate responses in a specific format, which minimizes extraneous text and focuses on producing the exact entity or fact required by the question. This in-context learning approach helps to align the model’s output with the strict requirements of the EM metric.

E COMPUTATIONAL COST ANALYSIS

Table 2: Computational cost per sample for each iteration of the MIRAG framework

Iteration	API Time (s)	Retrieval Time (s)
Iteration 0	7.96	15.23
Iteration 1	19.89	46.36
Iteration 2	32.29	79.74
Iteration 3	41.71	105.384

We analyze the per-sample computational cost of MI-RAG on a commodity server (NVIDIA RTX 3090, Intel Xeon Gold 6248R), performing retrieval locally and using the OpenRouter API OpenRouter (2025) for MLLM inference. As detailed in Table 2, both API and retrieval times scale linearly with each iteration, an expected characteristic of our design. Specifically, API time may increase as accumulated reasoning records lengthen the context for query generation, while retrieval time grows due to the increased processing required to encode these context-enriched queries. Crucially, this latency is not a fundamental limitation of our framework. The overhead stems from primarily from serialized execution of queries using vanilla index configurations and network overhead from successive API calls with multiple images and texts.

F QUERY STRATEGY ANALYSIS

In this section, we analyze the contributions of each query strategy to retrieval performance on the heterogeneous KB. Query expansion proves highly effective at retrieving directly related information, achieving 93.08% recall. In contrast, query generation is designed to explore complementary

```

1 Answer the knowledge-intensive question based on the provided image and
  ↳ context.
2 Generate a concise and accurate answer grounded in the retrieved
  ↳ information.
3 Use the context to support reasoning, and directly output the final
  ↳ answer.
4
5 There are 3 examples are shown below:
6
7 ##Example 1:
8 [Image 1 Content]
9 ##Context: {few_shot_context_1}
10 ##Question: {few_shot_question_1}
11 ##Best Answer: {few_shot_answer_1}
12
13 ##Example 2:
14 [Image 2 Content]
15 ##Context: {few_shot_context_2}
16 ##Question: {few_shot_question_2}
17 ##Best Answer: {few_shot_answer_2}
18
19 ##Example 3:
20 [Image 3 Content]
21 ##Context: {few_shot_context_3}
22 ##Question: {few_shot_question_3}
23 ##Best Answer: {few_shot_answer_3}
24
25 Now, answer this question
26 [Main Image Content]
27 ##Context: {reasoning records}
28 ##Question: {question}
29 ##Best Answer:

```

Figure 3: The few-shot prompt template used to guide the model for the Exact Match evaluation.

Table 3: Analysis of each query formulation’s contributions to retrieval recall from each KB on the InfoSeek validation subset.

Method	Multimodal KB Recall (%)	Textual KB Recall (%)	Hetero. KB Recall (%)
Query Expansion	90.02	87.44	93.08
Query Generation	88.24	80.03	90.80
Multi-Query	90.50	90.02	94.36

reasoning paths. Because its retrieval budget is restricted across two generated sub-queries compared to the query expansion, its recall is slightly lower. However, its primary value lies in finding a diverse set of factual links that a direct expansion might overlook.

G QUERY TRANSFORMATION VS. REASONING

Table 4: Impact of allocating a larger model (Gemini-2.5-Flash) to either the query transformation or reasoning records generation, while a lighter model (Gemma-3-4B) handles the other. Evaluated on the InfoSeek validation subset.

Query Transformation	Reasoning Generation	Acc (%)	Recall (%)
Gemma-3-4B	Gemini-2.5-Flash	56.36	91.63
Gemini-2.5-Flash	Gemma-3-4B	54.59	93.56

To assess which component of our framework benefits from increased model capacity, we performed an analysis by switching a lightweight model (Gemma-3-4B) and a more powerful model (Gemini-2.5-Flash) across the query transformation and reasoning generation. As shown in Table 4, allocating a more capable model to query transformation yields higher recall, likely due to improved query precision and diversity. However, placing the large model in the reasoning records generation results in higher overall accuracy, indicating that reasoning records using a powerful model provide more benefit for final accuracy.